

GOAL CHEMICAL SEALANTS CORP. -- GC-408 CLASS A -- 8030-00-007-8337

===== Product Identification =====

Product ID:GC-408 CLASS A

MSDS Date:01/01/1985

FSC:8030

NIIN:00-007-8337

Kit Part:Y

MSDS Number: BCVCT

=== Responsible Party ===

Company Name:GOAL CHEMICAL SEALANTS CORP.

Emergency Phone Num:(213) 269-0461

CAGE:04011

=== Contractor Identification ===

Company Name:GOAL CHEMICAL SEALANTS CORP

Addre

ss:3137 E 26TH ST

Box:City:LOS ANGELES

State:CA

ZIP:90023-4206

Country:US

Phone:213-269-0461

CAGE:04011

===== Composition/Information on Ingredients =====

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 31.2%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:POLYSULFIDE

Fraction by Wt: 56.2%

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 12.6%

OSHA PEL:200 PPM/150 STEL

ACGIH

TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:THIRAM (SARA III)  
CAS:137-26-8  
RTECS #:JO1400000  
Fraction by Wt: 0.20%  
OSHA PEL:5 MG/M3  
ACGIH TLV:1 MG/M3; 9192  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:MANGANESE DIOXIDE (AS MANGANESE)  
CAS:1313-13-9  
RTECS #:OP0350000  
OSHA PEL:C,5 MG/M3/1 FUME TWA  
ACGIH TLV:5 MG/M3 DUST/1 FUME

=====  
Hazards Identification =====

Effects of Overexposure:EYE,SKIN:IRRITATION;INHALE:DIZZINESS DUE TO  
TOLUENE.

=====  
First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR;SKIN,EYES:FLUSH W/LARGE AMOUNT OF  
WATER;INGEST:ADMINISTER EMETIC. CALL DR.NOTE:WASH SKIN AFTER EACH  
USE WITH SOAP AND WATER.

=====  
Fire Fighting Measures =====

Flash Point:77F,25C OC  
Extinguishing Media:CO\*2, H\*2O, ETC.  
Fire Fighting Procedures:NO SPECIAL PROCEDURES  
Unusual Fire/Explosion Hazard:NO UNUSUAL HAZARD

=====  
Accidental Release Measures =====

Spill Release Procedures:GENERAL CLEAN-UP SCRAPE UP EXCESS MATERIAL,  
CLEAN RESIDUE W/SOLVENT

=====  
Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F.

=====  
Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED-SOLVENT VAPORS. USE NIOSH/MSHA  
APPROVD DEVICE  
Ventilation:MFR RECM LOCAL EXHAUST  
Protective Gloves:RECOMMENDED  
Eye Protectio

n:RECOMMENDED

Other Protective Equipment:NO SPECIAL EQUIPMENT BESIDES ABOVE.

Supplemental Safety and Health

THE DRYING TIME VARIES FROM 1/2 HOUR TO 2 HOURS DEPENDING ON THE AMOUNT OF MANGANESE DIOXIDE ADDED TO THE PRODUCT.PART A OF A TWO PART KIT.KEY1:F4.

===== Physical/Chemical Properties =====

HCC:F4

Spec Gravity:1.47

Appearance and Odor:LIGHT TO DARK GREY WHEN MIXED; MERCAPTAN

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid:YES

Stability Condition to Avoid:TEMPERATURES ABOVE 300 F

Hazardous Decomposition Products:SO\*2,H\*2S, AND OTHER SULFUR COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM GENTERAL TRASH DISPOSAL. DISPOSE IAW FED.,STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.