View NSN Online: https://aerobasegroup.com/nsn/8030-00-008-7200

ESSEX CHEM.CORP.SPECIALTY CHEM.DIV. -- PRO-SEAL 870B-2 -- 8030-00-008-7200

Product ID:PRO-SEAL 870B-2 MSDS Date:01/01/1985 FSC:8030 NIIN:00-008-7200 Kit Part:Y MSDS Number: BCVDK === Responsible Party === Company Name: ESSEX CHEM.CORP.SPECIALTY CHEM.DIV. Emergency Phone Num:213-537-7600 CAGE: JO802 === Contractor Identification === Company Name: ESSEX CHEM.CORP.SPE CIALTY CHEM.DIV. CAGE: JO802 Company Name: ESSEX CHEMICAL CORP PRO-SEAL DIV Address:19451 SUSANA RD Box:City:COMPTON State:CA ZIP:90221-5713 Country:US Phone:310-537-7600 CAGE:83527

Ingred Name:POLYSULFIDE POLYMER Fraction by Wt: UNK

Ingred Name:PHENOLIC RESIN Fraction by Wt: UNK

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: UNK OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:STEARIC ACID CAS:57-11-4 RTECS #:WI2800000 Fraction by Wt: UNK

Ingred Name:SULFUR CAS:7704-34-9 RTECS #:WS4250000 Fraction by Wt: UNK

Effects of Overexposure: MAY CAUSE SKIN OR EYE IRRITATION UPON CONTACT.

First Aid:SKIN:WASH THOROUGHLY W/MILD SOAP AND WATER. EYES:IMMEDIATELY FLUSH W/WATER AT LEAST 15 MINUTES. CA LL MD. INGESTION:GIVE EMETIC.

CALL MD.

Flash Point:>230F CC Extinguishing Media:WATER, CO\*2, DRY CHEMICAL Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: CLEAN SPILLAGE W/RAGS OR SWEEPING COMPOUND AND SOLVENTS, TAKING PRECAUTIONS FOR FIRE AND INHALATION HAZARDS.

================= Handling and Storage

Handling and Storage Precautions: WASH HANDS AFTER HANDLING. Other Precautions: NONE

Ventilation:MECHANICAL-RECOMMENDED Protective Gloves:RECOMMENDED Eye Protection:RECOMMENDED Supplemental Safety and Health NAME:MERCAPTAIN TERMINATED POLYSULFIDE POLYMER;MEETS MIL-S-81733,TYPE II-2;PART A OF TWO PART PRODUCT, MFG GIVES LD50 0.5 T05 G/KG ORAL,RAT;CONTAINS CACO\*3,"IRCOGEL". KEY1:N1.

\_\_\_\_\_

HCC:N1 Boiling Pt:B.P. Text:450F Spec Gravity:1.38

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:STORE BELOW 80F

Waste Disposal Methods:MFR SUGGESTS NORMAL NONHAZARDOUS TRASH DISPOSAL OR FREFERABLE BURN WASTE.

Disclaimer (provided with this information by the compiling a gencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.