View NSN Online: https://aerobasegroup.com/nsn/8030-00-008-7207

Product ID:PR-1436-G CLASS A MSDS Date:01/01/1985 FSC:8030 NIIN:00-008-7207 Kit Part:Y MSDS Number: BCVDX === Responsible Party === **Company Name: PRODUCT RESEARCH & CHEMICAL CORPORATION** Address:5430 SAN FERNANDO ROAD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Num :818-240-2060 Emergency Phone Num:818-240-2060 CAGE:DO551 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574 Company Name: PRODUCT RESEARCH & CHEMICAL CORP. Address:5430 SAN FERNANDO RD./P.O. BOX 1800 Box:1800 City:GLENDALE State:CA ZIP:91209 Phone:800-228-5635 CAGE:DO551

======= Composition/Information on Ingredients =======

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 12.0% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:CALCIUM DICHROMATE CAS:14307-33-6 RTECS #:HX7630000 Fraction by Wt: 5.0% OSHA PEL:C, 0.1 MG/M3 (CRO3) ACGIH TLV:0.05 MG/M3 (CR);8990

Ingred Name:DIMETHYLFORMAMIDE CAS:68-12-2 RTECS #:LQ2100000 Fraction by Wt: 3.0% OSHA PEL:S, 10 PPM ACGIH TLV:S, 10 PPM; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred N ame:METALLIC CHROMATE Fraction by Wt: 3.0% OSHA PEL:C, 0.1 MG/M3 (CRO3) ACGIH TLV:0.05 MG/M3 (CR);8990

Effects of Overexposure:SKIN IRRITANT.THE BASE COMPOUND & ACCELERATOR CONTAINS CHROMATES WHICH MAY BE ABSORBED THROUGH SKIN.

First Aid:SKIN:WASH THOROUGHLY W SOAP & WATER;EYES:WASH OUT IMMEDIATELY W PLENTY OF WATER.GET MEDICAL ATTENTION;INHALATION

:REMOVE AFFECTED INDIVIDUAL TO FRESH AIR;INGESTION:IMMEDIATELY GET MEDICAL HELP.

Flash Point:50F,10C PMCC Lower Limits:UNK Upper Limits:UNK Extinguishing Media:ANY EXTINGUISHER APPROVED FOR CLASS B FIRES Fire Fighting Procedures:NONE KNOWN Unusual Fire/Explosion Hazard:CAN EMIT POTENTIALLY TOXIC VAPORS.

Spill Release Procedures:WIPE UP W RAGS/PAPER TOWE LS.CLEAN SURFACE/AREA W MEK USING APPROPRIATE PROTECTIVE EQUIPMENTS;LARGE SPILL;ELIMINATE IGN SOURCES,STOP LEAK,& DIKE SPILL AREA.TRANSFER SPILL WASTE INTO SALVAGE TANK FOR DI SPOSAL.

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS IN COOL DRY AREA.PROTECT CONTAINER AGAINST PHYSICAL DAMAGE.KEEP AWAY FROM HEAT,FLAME,ETC. Other Precautions:AVOID PROLONGED OR REPEATED SKIN CONTACT.

===== Exposure Controls/Personal Protection =========

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS. Ventilation:LOCAL EXHAUST TO MINIMIZE VAPOR CONCENTRATION. Protective Gloves:POLYETHYLENE Eye Protection:CHEMICAL GOGGLES Other Protective Equipment:PROTECTIVE HAND CREAM MAY BE USED Supplemental Safety and Health

HCC:F2 Spec Gravity:1.35 Solubility in Water:NEGLIGIBLE Appearance and Odor:ALUMINUM-GRAY SY RUP, SLIGHT TOLUENE ODOR Percent Volatiles by Volume: 17.0

Stability Indicator/Materials to Avoid:YES CORROSIVE & OXIDIZING MATERIAL Stability Condition to Avoid:SOURCE OF IGNITION Hazardous Decomposition Products:OXIDES OF SULFUR,HYDROGEN SULFIDE,FORMIC ACID

Waste Disposal Methods:DO NOT INCINERATE THE WASTE & CONTAINERS(EMPTY/FULL)OF THE PRODUCT.DISP OSE OF WASTE IN TIGHTLY CLOSED CONTAINERS IAW LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assu

me responsibility for the suitability of this information to their particular situation.