

DAVIS-HOWLAND OIL CORP -- MIL-L-15019E,MIL SYNMBL6135,LUBE OIL,COMPDE --  
9150-00-011-5892

=====  
===== Product Identification =====

Product ID:MIL-L-15019E,MIL SYNMBL6135,LUBE OIL,COMPDE

MSDS Date:01/01/1985

FSC:9150

NIIN:00-011-5892

MSDS Number: BCVHJ

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORP

Emergency Phone Num:(716) 473-6650

CAGE:FO626

=== Contractor Identification ===

Company Name

e:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBONS(COMPLEX MIXTURE)

Fraction by Wt: 100%

=====  
===== Hazards Identification =====

Effects of Overexposu

re:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE  
MILD SKIN IRRITATION;MAY CAUSE EYE IRRITATION.

===== First Aid Measures =====

First Aid:IN CASE OF SKIN CONTACT,WASH WITH SOAP & WATER;IF SPLASHED  
INTO EYES FLUSH WITH CLEAR WATER UNTIL IRRITATION SUBSIDES.GET MED  
ATTN FOR EYES.

===== Fire Fighting Measures =====

Flash Point:560F-(COC)

Lower Limits:1.0%

Upper Limits:6.0%

Extinguishing Media:FOAM,DRY CHEMICAL,CO\*  
2,H\*20 SPRAY OR FOG.

Fire Fighting Procedures:USE AIR-SUPPLD RESCUE EQUIP IN CLOSED  
AREA;COOL CONT W/H\*20

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQD.ADD  
ABSORBENT(SAND,EARTH,SAWDUST,ETC)TO SPILL AREA;KEEP PETROLEUM  
PRODUCTS OUT OF SEWER & WATER COURSES BY DIKING OR IMPOUNDED.ADVISE  
AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS,WAT  
ER  
COURSES OR EXTENSIVE LAND AREAS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN  
USE;KEEP AWAY FROM HEAT & OPEN FLAMES,SPARKS OR STRONG OXIDANTS.

Other Precautions:AVOID BREATHING OIL MIST.REMOVE OIL-SOAKED CLOTHING &  
LAUNDRER BEFORE RE-USE.WASH THOROUGHLY W/SOAP & H\*20 AFTER  
HANDLING/EXPOSURE;DO NOT HANDLE NEAR HEAT,SPARKS,FLAME OR STRONG  
OXIDANTS.

===== Exposure Controls/Pe  
rsonal Protection =====

Respiratory Protection:NORMLLY NOT NEEDED.USE SUPPLD-AIR RESP IN  
CONFINED/ENCLOSED SPACES.

Ventilation:LOCAL EXHAUST:TO CAPTURE HOT FUMES & VAPORS.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:USE CHEM RESISTNT APRON/CLOTHNG IF NEEDED TO  
AVOID CONT

Supplemental Safety and Health

MSDS NOT DATED;ITEM IS MILITARY SYMBOL 6135,UNDER  
MIL-L-15019E,LUBRICATING OIL COMPOUNDED.

===== Physical/Chemica

I Properties =====

HCC:V6

Boiling Pt:B.P. Text:750F

Vapor Pres:.01

Vapor Density:>20

Spec Gravity:0.90

Evaporation Rate & Reference: