

KAMAN AEROSPACE CORP -- MS 9134-01 GASKET, ASBESTOS-RUBBER -- 5330-00-023-7623

=====
Product Identification
=====

Product ID:MS 9134-01 GASKET, ASBESTOS-RUBBER

MSDS Date:01/01/1987

FSC:5330

NIIN:00-023-7623

MSDS Number: BCVNB

=== Responsible Party ===

Company Name:KAMAN AEROSPACE CORP

Emergency Phone Num:203-242-4461

CAGE:84955

=== Contractor Identification ===

Company Name:KAMAN AEROSPACE CORP

A

Address:OLD WINDSOR ROAD

Box:City:BLOOMFIELD

State:CT

ZIP:06002

Country:US

Phone:203-242-4164

CAGE:84955

=====
Composition/Information on Ingredients
=====

Ingredient Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Fraction by Wt: 100%

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9192

=====
Hazards Identification
=====

Effects of Overexposure:PARTICLE MAT: IRRIT OF RESP TRACT,SKIN & EYE.
CHRONIC INHALATION OF PARTICLE CAN PRODUCE
ASBESTOSIS.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES,CONSULT PHYSICIAN. SKIN:
FLUSH WITH WATER. INHALATION: REMOVE FROM EXPOSURE.

=====
Fire Fighting Measures
=====

Flash Point:NONE

Extinguishing Media:AS APPROPRIATE FOR THE SURROUNDING MATERIAL.

=====
Accidental Release Measures
=====

Spill Release Procedures:EXCLUDE ALL FROM SPILL AREA EXCEPT TRAINED

CLEAN-UP CREW. PROVIDE EXHAUST VENT WITH CAPTURE FILTRATION. DO NOT STIR UP DUST. USE WET METHOD OR APPROVED VACUUM CLEANING SYSTEM TO PICK UP SPILL. PLACE WASTE IN DUST-TIGHT CONTAINER/PLASTIC BAG,& LABEL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DUST TIGHT CONTAINER IN CLEAN,SCURE AREA. USE DUST SUPPRESSION CONTROL AT ALL STAGES OF HANDLING,USE AND DISPOSAL.
Other Precautions:AVOID INHALATION FO ASBEST OS. MONITOR WORK AREAS FOR EXPOSURE LEVELS. RETAIN MEDICAL RECORDS OF WORKERS FOR AT LEAST 20 YEARS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.
Ventilation:LOCAL/MECHANICAL WITH CAPTURE FILTRATION
Other Protective Equipment:BODY-COVERING WORK CLTIH,SPECIAL VACUUMING FACILITY FOR CLOT
Supplemental Safety and Health
UPDATED PER NON-OSHA MSDS RECD 2MAY85.

=====
===== Physical/Chemical Properties =====

HCC:T6
Boiling Pt:B.P. Text:DECOMPOSES
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WHITE OR LIGHT GREY FIBERS.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

=====
===== Disposal Considerations =====

Waste Disposal Methods:DEPOSIT IN SECURED LANDFILL WHERE ASBESTOS WILL REMAIN BURIED. FOLLOW LOCAL,STATE AND FEDERAL REGULATIONS.

Dis

claimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.