

EUTECTIC CORP -- XUPER 18 XFC -- 3439-00-027-0948

=====
Product Identification
=====

Product ID:XUPER 18 XFC
MSDS Date:08/07/1990
FSC:3439
NIIN:00-027-0948
MSDS Number: BCVQG
=== Responsible Party ===
Company Name:EUTECTIC CORP
Address:40-40 172ND STREET
City:FLUSHING
State:NY
ZIP:11358-9981
Country:US
Info Phone Num:718-358-4000 FAX: 718-445-1784
Emergency Phone Num:718-358-4000
CAGE:72271

===

Contractor Identification ===
Company Name:EUTECTIC CORP
Address:9625-J SOUTHERN PINE BLVD
Box:City:CHARLOTTE
State:NC
ZIP:28273
Country:US
Phone:704-527-9800/ 800-221-1433
CAGE:72271

=====
Composition/Information on Ingredients
=====

Ingred Name:COPPER (SARA III)
CAS:7440-50-8
RTECS #:GL5325000
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2MG/M3 FUME; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
OSHA PEL:10 MG ZNO

/M3
ACGIH TLV:10 MG ZNO/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BORIC ACID
CAS:10043-35-3
RTECS #:ED4550000
OSHA PEL:15 MG/CUM
ACGIH TLV:10 MG/CUM

Ingred Name:ACRYLIC RESINS
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3

Ingred Name:NICKEL (SARA III)
CAS:7440-02-0
RTECS #:QR5950000
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192

===== Hazards Identification =====

LD50 LC50 Mixture:UNCLASSIFIED BRAZING FUMES=5MG/M3 PEL
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EXPOSURE TO BRAZING FUMES OR GASES MAY CAUSE METAL FUME FEVER. SYMPTOMS INCLUDE NAUSEA, FEVER, DRYNESS OR IRRITATION OF THE THROAT, COUGHING, BODY ACHE AND CHILLS. LONG TERM EXPOSURE TO BRAZING FUMES, GASES OR DUST MAY CONTRIBUTE TO PULMONARY IRRITATION OR PNEUMOCONIOSIS. USE OF FLUORIDE FLUX FUMES ARE ALSO HAZARDOUS.

Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS ALLOY ARE CONSIDERED CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:COPPER AND ZINC FUME MAY CAUSE METAL FUME FEVER. SHORT TERM SYMPTOMS MAY INCLUDE A METALLIC TASTE IN THE MOUTH, DRYNESS OR IRRITATIONS OF THE THROAT FOLLOWED BY COUGHING, SHORTNESS OF BREATH, NAUSEA, FEVER, BODY ACHE, AND CHILLS. LONG TERM EXPOSURE TO WELDING FUME, GASES OR DUST MAY CONTRIBUTE TO PULMONARY IRRITATION.

Me

dical Cond Aggravated by Exposure:INDIVIDUALS WITH IMPAIRED PULMONARY FUNCTIONS OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY FUME IRRITATIONS.

=====
===== First Aid Measures =====

First Aid:REMOVE FROM DUST OR FUME EXPOSURE. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION IMMEDIATELY. BRAZING ALLOYS ARE FREQUENTLY USED WITH A FLUORIDE TYPE FLUX. IF APPLICABLE, FLUX FUME SHOULD BE CONSIDERED IN TREATMENT.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp Text:NONE
Extinguishing Media:NONFLAMMABLE. WELDING ARC & SPARKS & BRAZING FLAMES CAN IGNITE COMBUSTIBLES AND FLAMMABLES. USE MEDIA FOR SPECIFIC FIRE.
Fire Fighting Procedures:REFER TO ANSI Z49.1 FOR FIRE PREVENTION DURING THE USE OF WELDING AND ALLIED PROCEDURES.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSURE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR BRAZING.
Other Precautions:PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR BRAZING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE

ONLY NIOSH APPROVED RESPIRATORS.

Ventilation:USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR BRAZING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE

Protective Gloves:WELDERS LEATHER GLOVES

Eye Protection:OSHA APPROVED GOGGLES/FACE SHIELD W/LENS

Other Protective Equipment:DARK FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR BRAZING INCLUDING ARM & SHOULDER PROTECTORS, APRON, AND HAT.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING, DRINKING OR SMOKING. L

AUNDER CONTAMINATIED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

BRAZING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR ELECTRODES USED. OTHER INFL UENCING FACTORS ARE THE PRESENCE OF CONTAMINANTS. CHLORINATED SOLVENTS AND FLUORIDE FLUXES MAY DECOMPOSE TO TOXIC GASES.

===== Physical/Chemical Properties =====

HCC:N1

Solub

ility in Water:NEGLIGIBLE

Appearance and Odor:WELDING ROD, FLUX COATED.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:BRAZING FUMES AND GASES CANNOT BE CLASSIFIED SIMPLY. THE DECOMPOSITON PRODUCTS ARE DIFFERENT FROM THE ROD INGREDIENTS.

===== Disposal Considerations =====

Waste Disposal M

ethods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume respo

nsibility for the suitability of this information to their particular situation.