

CORICONE CORP. -- CORICONE 1700 -- 8030-00-033-4291

=====  
Product Identification  
=====

Product ID:CORICONE 1700

MSDS Date:01/01/1985

FSC:8030

NIIN:00-033-4291

MSDS Number: BCVSX

=== Responsible Party ===

Company Name:CORICONE CORP.

Emergency Phone Num:312-441-5800

CAGE:JO858

=== Contractor Identification ===

Company Name:CORICONE CORP

Address:550 FRONTAGE RD

Box:City:NORTHFIELD

State:IL

ZIP:60093

-1202

Country:US

CAGE:25807

Company Name:CORICONE CORP.

CAGE:JO858

=====  
Composition/Information on Ingredients  
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ORGANIC RESIN

S(10-20%)

===== Hazards Identification =====

Effects of Overexposure:EYE IRRIT. INH: HDCH, DIZ, NAUSEA. SKIN:  
BURNING SENSATION UPON CONTINUOUS EXPOSURE.

===== First Aid Measures =====

First Aid:EYES:FLUSH W/WATER. SKIN:FLUSH W/WATER OR MILD SOAP & WATER.  
INHAL:MOVE TO FRESH AIR. IF SYMPTOM CONTINUE SEE DR.

===== Fire Fighting Measures =====

Flash Point:90F OC  
Lower Limits:1.0  
Upper Limits:6.0  
Extinguishing Media:WATER SPRAY  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH W/ WATER INTO RETAINING AREA OR  
CONTAINER OR COVER W/SAND OR DRY CHEMICALS.AVOID EXPOSURE TO  
SPARKS,FIRE OR HOT METAL SURFACES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 120 F IN TIGHTLY SEALED  
CONTAN  
ER.USE W/ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED  
CONTACT WITH SKIN.  
Other Precautions:KEEP AWAY FROM HEAT,SPARKS,OPEN FLAME & FIRE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD SELF-CONTAINED BRTHNG APPAR  
FOR CONC ABOVE TLV.  
Ventilation:POSITIVE AIR VENTILATION.AIR SUPPLIED HOOD  
Protective Gloves:BUNA-N RUBBER  
Eye Protection:GLASSES OR GOGGLES  
Other Protective Equipment:ALSO CAN USE POLY ETHYLENE PLASTIC GLOVES.

S

Supplemental Safety and Health

VAPOR PRESSURE: 0.5.% VOLATILE BY VOLUME: 80 TO 90

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:285-290F

Vapor Density:3.7

Spec Gravity:0.902

Appearance and Odor:AMBER COLOR-ODOR MEDIUM TO STRONG

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT,SPARKS,OPEN FLAME,FIRE

Hazardous Decomposition Products:THERMAL DECOMP MA

Y YIELD CARBON

MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM INCINERATE UNDER SAFE CONDITIONS OR  
DISPOSE OF IAW FED,STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims

all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.