

DAVIS HOWLAND OIL CORP -- MIL-L-83767B;LUBRICATING OIL -- 9150-00-050-4556

=====
Product Identification
=====

Product ID:MIL-L-83767B;LUBRICATING OIL

MSDS Date:01/01/1987

FSC:9150

NIIN:00-050-4556

MSDS Number: BCWBV

=== Responsible Party ===

Company Name:DAVIS HOWLAND OIL CORP

Address:200 ANDERSON AVE

City:ROCHESTER

State:NY

ZIP:14607-1111

Country:US

Info Phone Num:716-473-6650

Emergency Phone Nu

m:716-473-6650

CAGE:5A565

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Other REC Limits:5MG/CUM,AS OIL MIST

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES (TYPE NOT SPECIFIED)

=====

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES OR SKIN.
CHRONIC:NO DATA AVAILABLE.
Effects of Overexposure:MAY CAUSE EYE IRRITATION:MILD IRRITATION OF
SKIN ON PROLONGED OR REPEATED CONTACT.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

=====
First Aid Measures
=====

First Aid:EYES:WASH WITH
H PLENTY OF WATER,CALL A PHYSICIAN. SKIN:WASH
WITH SOAP & WATER THOROUGHLY. INHALATION:REMOVE TO FRESH AIR,CALL A
PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:395-475F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,FOG
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

=====
Accidental Release Measures
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE
LIQUID;USE SUITABLE ABSORBENT MATERIAL AND RECOVER FOR PROPER
DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED
AREA;KEEP AWAY FROM HEAT & OPEN FLAME;DO NOT USE CONTAMINATED
CLOTHES.

=====
Exposure Controls/Personal Protection
=====

Respiratory

Protection:NOT NEEDED IF THERE IS ADEQUATE VENTILATION.

Ventilation:LOCAL/GENERAL TO MAINTAIN BELOW TLV/PEL

Protective Gloves:IMPERVIOUS OR AS REQUIRED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:OIL IMPERVIOUS,APRON,BOOTS

Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES;WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

THIS NSN IS NON STANDARD;REPLACED BY NSN 9150-00-273-8663.

===== Physical/Chemical Properties =====

HCC:V6

Bo

iling Pt:B.P. Text:545-900F

Vapor Pres:12.0

Spec Gravity:0.87-0.95

Evaporation Rate & Reference: