View NSN Online: https://aerobasegroup.com/nsn/8010-00-055-5182

CORONADO PAINT COMPANY INC. -- PRIMER COATING, 34554 GREEN -- 8010-00-055-5182 Product ID:PRIMER COATING, 34554 GREEN MSDS Date:01/01/1985

FSC:8010

NIIN:00-055-5182

MSDS Number: BCWJX === Responsible Party ===

Company Name: CORONADO PAINT COMPANY INC.

CAGE:33200

=== Contractor Identification ===

Company Name: CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROA

Box:City:EDGEWATER

State:FL

ZIP:32132-1812 Country:US

Phone:904-428-6461

CAGE:33200

====== Composition/Information on Ingredients ========

Ingred Name:LINSEED & ALKYD RESINS

Fraction by Wt: 26%

Ingred Name: AROMATIC & ALIPHATIC HYDROCARBONS

Fraction by Wt: 20% **ACGIH TLV:100PPM**

Ingred Name:LEAD NAPHTHENATE

Fraction by Wt: 0.5%

========== Hazards Identification ===============

Effects of Overexposure: SEVERE EYE IRRITATION, DRYING OF SKIN. **EXCESSIVE INHAL**

| ATION CAUSES HEADACHE, DIZZINESS, NAUSEA. |
|--|
| ====================================== |
| First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH MILD SOAP AND WATER AND APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR AND CALL A PHYSICIAN, APPLY ARTIFICIAL RESPIRATION IF NECESSARY. |
| ====================================== |
| Flash Point:90F, SETA Lower Limits:0.9 Upper Limits:7.0 Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL Fire Fig hting Procedures:TREAT AS CLASS B FIRE. Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR. |
| ========= Accidental Release Measures ========== |
| Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSUREO SPARKS, FIRE OR HOT METAL SURFACES. |
| ====================================== |
| Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE W ITH ADEQUATE VENTILATION. AVOID PROLONGED OREPEATED CONTACT WITH SKIN. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED Ventilation:LOCAL EXHAUST Protective Gloves:YES Eye Protection:YES Other Protective Equipment:EYE BATH AND SAFETY SHOWER. Supplemental Safety and Health 308 OLD COUNTRY ROAD, EDGEWATER, FLORIDA 32032. |
| ====================================== |

HCC:F3

Boiling Pt:B.P. Text:240F

Vapor Pres:6

Vapor Density:3.7

Spec Gravity:1.35

Evaporation Rate & Evaporation R

Solubility in Water: VERY SLIGHT

Appearance and Odor:GREEN OPAQUE LIQUID, PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume:38

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES OR FIRE.
Hazardous Decomposition Products:TH
ERMAL DECOMPOSITION MAY YIELD CARBON
MONOXIDE

======= Disposal Considerations ============

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims al

I liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.