View NSN Online: https://aerobasegroup.com/nsn/8030-00-059-2761

FEL-PRO, INC -- FEL-PRO C5-A -- 8030-00-059-2761

Product ID:FEL-PRO C5-A MSDS Date:01/01/1985

FSC:8030

NIIN:00-059-2761

MSDS Number: BCWNZ === Responsible Party === Company Name:FEL-PRO, INC

Emergency Phone Num:312-761-4500

CAGE:JO924

=== Contractor Identification ===

Company Name: FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

Address:7450 N MCCORMICK

Box:1103 City:SKO KIE

State:IL

ZIP:60076-4046

Country:US

Phone:847-674-7700 OR 312-761-4500

CAGE:73165

Company Name: FEL-PRO, INC

CAGE:JO924

====== Composition/Information on Ingredients ========

Ingred Name: COPPER (SARA III)

CAS:7440-50-8

RTECS #:GL5325000

OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: GRAPHITE (UNKNOWN PERCENT)

RTECS #:VV7780000

Ingred Name: PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS#

ACGIH TLV:400 PPM; 8990
======================================
Effects of Overexposure:AVOID EYE CONTACT. AVOID INGESTION.
======================================
First Aid:INGESTION: CALL MD IMMEDIATELY. EYE: IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN. CALL MD. SKIN: WASH W/MILD SOAP AND WATER.
======================================
Flash Point:ASTM D92-57 310F Extinguis
hing Media:CO*2, DRY CHEMICALS Fire Fighting Procedures:SAME AS FOR PETROLUEM GREASE FIRES Unusual Fire/Explosion Hazard:NONE
======== Accidental Release Measures ==========
Spill Release Procedures:WIPE UP W/RAGS - SHOVEL, SCRAPE - FINISH CLEANING W/DETERGENT & WATER OR HIGH FLASH POINT CLEANER W/VENTILATION.(MFG REC)
=========== Handling and Storage ===========
Handling and Storage Precautions:NORMAL STORAGE AND HANDLING. MAINTAIN GOOD PERSONAL HYGIENE.
====== Exposure Controls/Personal Protection ========
Protective Gloves:NOT NEEDED Eye Protection:RECOMMENDED, BUT NOT NEED Supplemental Safety and Health MFG LISTS VAPOR PRESS, EVAP RATE, % VOLATILE BY VOLUME TO BE NIL
Eye Protection:RECOMMENDED, BUT NOT NEED Supplemental Safety and Health
Eye Protection:RECOMMENDED, BUT NOT NEED Supplemental Safety and Health MFG LISTS VAPOR PRESS, EVAP RATE, % VOLATILE BY VOLUME TO BE NIL

:SE7449000

OSHA PEL:400 PPM

ty and Reactivity Data ========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS, CHEMICALLY UNSTABLE COMPOUNDS Hazardous Decomposition Products:NONE

======= Disposal Considerations ==========

Waste Disposal Methods: NORMAL FOR GREASE PRODUCTS. IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Def

ense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.