

THE DEXTER CORP -- EPK 0151, EPOXY PATCH KIT PART B, AB0151 -- 8040-00-059-5477

=====  
Product Identification  
=====

Product ID:EPK 0151, EPOXY PATCH KIT PART B, AB0151

MSDS Date:12/19/1988

FSC:8040

NIIN:00-059-5477

Kit Part:Y

MSDS Number: BCWPJ

=== Responsible Party ===

Company Name:THE DEXTER CORP

Address:ONE DEXTER DRIVE

City:SEABROOK

State:NH

ZIP:03874

Country:US

Info Phone Num:603-474-5541

Eme

rgency Phone Num:603-926-0910

Preparer's Name:DR. SHELDON CLARK

CAGE:HO354

=== Contractor Identification ===

Company Name:DEXTER CORP DEXTER ELECTRONIC MATERIALS DIV

Address:15051 E DON JULIAN RD

Box:City:LA PUENTE

State:CA

ZIP:91746

Country:US

Phone:818-968-6511

CAGE:12405

Company Name:THE DEXTER CORP

Address:ONE E WATER ST

Box:1282

City:WAUKEGAN

State:IL

ZIP:60085

Country:US

Phone:708-623-4200

CAGE:HO354

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NO INGR

EDIENT FOR THIS FORMULATION\_INGREDIENT

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:MATERIAL IS CORROSIVE TO SKIN. MAY  
CAUSE CHEMICAL BURNS TO SKIN AND EYES. REPEAT CONTACT MAY CAUSE  
SENSITIZATION. SIGNS & SYMPTOMS OF EXPOSURE:SKIN RASH, IRRITATION;  
POSSIBLE BURNS.  
Exp  
lanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:SEE HEALTH HAZARDS.

=====  
===== First Aid Measures =====

First Aid:INGEST:CALL MD IMMEDIATELY . INHAL:REMOVE TO FRESH AIR.  
SUPPORT BREATHING (GIVE O\*2/ARTF RESP) . EYES:IMMEDIATELY FLUSH  
W/POTABLE WATER FOR MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD  
( ). SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD .

=====  
===== Fire Fighting Measures =====

Flash Poi  
nt Method:COC  
Flash Point:265F,129C  
Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER  
SPRAY, FOAM OR FOG.  
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE  
EQUIPMENT .  
Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASSES MAY BE  
LIBERATED.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP EXCESS & TRANSFER TO METAL  
CONTAINERS. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING  
SOLVENT FLAMMABILITY CAUTIONS, OR USE DETERGENT.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL  
INSTRUCTIONS. FOLLOW RECOMMENDED CURING SCHEDULE.  
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED WITH GOOD INDUSTRIAL VENTILATION;  
NIOSH/MSHA A

PPRVD ORGANIC RESPIRATOR.

Ventilation:LOCAL EXHST: PREFERABLE. MECH: ACCEPTABLE

Protective Gloves:RUBBER/PLASTIC

Eye Protection:ANSI APPROVED CHEM SAFETY GOGGLES

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

EMERGENCY EYE BATH AND DELUGE SHOWER .

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FILLER PARTICLES ARE THOROUGHLY WETTED BY VEHICLE SO AIRBORNE EXPOSURE DOES NOT OCCUR UNLESS CURED MATERIAL IS SUBSEQUENTLY GROUND,

MACHINED OR SANDED. CNDTNS TO AVOID (POLYM):TO BE BONDED. FAILURE TO OBSERVE CAUTIONS MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH THE RELEASE OF TOXIC GASSES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:531F,277C

Vapor Pres:1

Spec Gravity:0.98

Evaporation Rate & Reference: