FSC:6850

NIIN:00-060-5312

MSDS Number: BCWQQ === Responsible Party ===

Company Name: PPG INDUSTRIES, INC

Address:1 PPG PL City:PITTSBURGH

State:PA ZIP:15272 Country:US CAGE:GO796

=== Contractor Identification ===

Company Name: PPG INDUSTRIES INC

Address:ONE P PG PLACE

Box:City:PITTSBURGH

State:PA ZIP:15272 Country:US

Phone:1-800-245-2974 (CAL HYPO)

CAGE:47695

Company Name: PPG INDUSTRIES, INC. COATINGS TRESINS DIV.

Address:1 PPG PL City:PITTSBURGH

State:PA ZIP:15272 Country:US CAGE:GO796

======= Composition/Information on Ingredients ========

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III)

CAS:109-86-4

RTECS #:KL5775000 Fraction by Wt: >99%. OSHA PEL:S, 25 PPM ACGIH TLV:S, 5 PPM; 9192

RTECS #:9999999ZZ

Ingred Name: 2,6 DITERTIARY BUTYL,4

-METHYPHENOL;OR 2,4 DIMETHYL,6-TERTIARY BUTYLPHENOL; OR RTECS #:9999999ZZ

Ingred Name:2,6 DITERTIARY BUTYLPHENOL; OR MIXED TERTIARY BUTYLPHENOL COMPOSITION)
RTECS #:9999992Z

Ingred Name: ANTIOXIDANT, (RANGE 50-150 PPM) SEE ABOVE FOR OPTIONS PERMITTED BY SPEC.

Effects of Overexposure:MILDLY IRRITATING TO EYES/SKIN.INHAL:CENTRAL NERV SYSTEM DEPRESSANT, CAUSES HEADACHE, -*SEE SUPP DATA

First Aid:EYES/SKIN:FLUSH W PLENTY OF WATER (SOAP & WATER FOR SKIN)FOR AT LEAST 15 MIN.GET MED ATTN.INHAL:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NECESSARY.INGESTN:GIVE A QT OF WATER,INDUCE VOMITING,GET MED ATTN .DO NOT INDUCE VOMITING/GIVE FOOD IF UNCONSCIOUS.

========== Fire Fighting Measures ===============

Flash Point:107F/41.7C TCC

Autoignition Temp: Autoignition Temp Text: 545F


Lower Limits:2.0% Upper Limits:14%

Ε

xtinguishing Media:CO*2,ALCOHOL TYPE FOAM OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:EGMME CAN FORM EXPLOSIVE PEROXIDE ON
CONTACT W AIR OVER LONG PERIODS;USE OF WATER MAY CAUSE FROTHING

========= Accidental Release Measures ============

Spill Release Procedures:IMMED REMOVE SOURCES OF IGN,WEAR PROTECTIVE EQUIP & VENTILATE AREA.DIKE AREA TO CONTAIN SPILL & PUMP TO SALVAGE TANK.ABSORB REMAINING LIQ



HCC:F4

Boiling Pt:B.P. Text:256F,124.5C

Vapor Pres:6.2

Vapor Density:2.62

Spec Gravity:0.966

Evaporation Rate & Reference: 0.5% (N-BU ACETATE)

Solubility in Water: COMPLETE

Appearance and Odor:CLEAR,COLORLESS LIQ W MILD AROMATIC ODOR.

Percent V

========== Stability and Reactivity Data ============
Stability Indicator/Materials to Avoid:YES OXIDIZING & CORR MATL;LONG-TERM CONTACT W AIR. Stability Condition to Avoid:SOURCE OF IGNITION Hazardous Decomposition Products:PROLONGED AIR CONTACT MAY FORM EXPLOSIVE PEROXIDE

olatiles by Volume:100

======= Disposal Considerations ===========

Waste Disposal Methods:BURN WASTE LIQ IN AN APPROVED INCINERATOR IAW EXISTING REGULATIONS.MATL ABSORBED ON A BSORBENT MATL SHOULD BE

BURIED IN A PERMITTED HAZ WASTE MANAGEMENT FACILITY IAW LOCAL, STATE & FED REGS/STATUTES REG ARDING DISPOSAL. TREAT DAMAGED/EMPTY CONTNR AS HAZ.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.