

PPG INDUSTRIES,INC -- ANTI-ICING AGENT -- 6850-00-060-5312

=====
Product Identification
=====

Product ID:ANTI-ICING AGENT

MSDS Date:01/01/1987

FSC:6850

NIIN:00-060-5312

MSDS Number: BCWQQ

=== Responsible Party ===

Company Name:PPG INDUSTRIES,INC

Address:1 PPG PL

City:PITTSBURGH

State:PA

ZIP:15272

Country:US

CAGE:GO796

=== Contractor Identification ===

Company Name:PPG INDUSTRIES INC

Address:ONE P

PG PLACE

Box:City:PITTSBURGH

State:PA

ZIP:15272

Country:US

Phone:1-800-245-2974 (CAL HYPO)

CAGE:47695

Company Name:PPG INDUSTRIES,INC. COATINGS TRESINS DIV.

Address:1 PPG PL

City:PITTSBURGH

State:PA

ZIP:15272

Country:US

CAGE:GO796

=====
Composition/Information on Ingredients
=====

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III)

CAS:109-86-4

RTECS #:KL5775000

Fraction by Wt: >99%.

OSHA PEL:S, 25 PPM

ACGIH TLV:S, 5 PPM; 9192

RTECS #:9999999ZZ

Ingred Name:2,6 DITERTIARY BUTYL,4

-METHYPHENOL;OR 2,4
DIMETHYL,6-TERTIARY BUTYLPHENOL; OR
RTECS #:9999999ZZ

Ingred Name:2,6 DITERTIARY BUTYLPHENOL; OR MIXED TERTIARY BUTYLPHENOL
COMPOSITION)
RTECS #:9999999ZZ

Ingred Name:ANTIOXIDANT,(RANGE 50-150 PPM) SEE ABOVE FOR OPTIONS
PERMITTED BY SPEC.

=====
===== Hazards Identification =====

Effects of Overexposure:MILDLY IRRITATING TO EYES/SKIN.INHAL:CENTRAL
NERV SYSTEM DEPRESSANT,CAUSES HEADACHE,-*SEE SUPP DATA

=====
===== Fi
rst Aid Measures =====

First Aid:EYES/SKIN:FLUSH W PLENTY OF WATER (SOAP & WATER FOR SKIN)FOR
AT LEAST 15 MIN.GET MED ATTN.INHAL:REMOVE TO FRESH AIR.GIVE
CPR/OXYGEN IF NECESSARY.INGESTN:GIVE A QT OF WATER,INDUCE
VOMITING,GET MED ATTN .DO NOT INDUCE VOMITING/GIVE FOOD IF
UNCONSCIOUS.

=====
===== Fire Fighting Measures =====

Flash Point:107F/41.7C TCC
Autoignition Temp:Autoignition Temp Text:545F
Lower Limits:2.0%
Upper Limits:14%

E
xtinguishing Media:CO*2,ALCOHOL TYPE FOAM OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:EGMME CAN FORM EXPLOSIVE PEROXIDE ON
CONTACT W AIR OVER LONG PERIODS;USE OF WATER MAY CAUSE FROTHING

=====
===== Accidental Release Measures =====

Spill Release Procedures:IMMED REMOVE SOURCES OF IGN,WEAR PROTECTIVE
EQUIP & VENTILATE AREA.DIKE AREA TO CONTAIN SPILL & PUMP TO SALVAGE
TANK.ABSORB REMAINING LIQ

ON ABSORBENT MATL & SHOVEL INTO CONTNRS
SUITABLE FOR SHIPMENT TO DISPOSAL AREA.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM SUNLIGHT,SOURCE OF
HEAT,IN WELL VENTILATED AREA.WEAR PROTECT CLOTHG IN
HANDLG/STORG.KEEP CONTNRS TIGHTLY CLOSED TO AVOID AIR CONTACT.
Other Precautions:AVOID BRTHN VAP/MISTS ABOVE TLV LIMITS;AVOID FREQUENT
CONT W SKIN,EYES & CLOTHING;USE ONLY W ADEQUATE VENTILATION;OBSERVE
ALL HA
Z PRECAUTIONS FOR EMPTY CONTNRS.GRD CONTNRS/SYSTEM BEFORE
UNLOAD

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CNTND BRTHG APP IN CONFINED AREA.ORG VAP
TYPE APPRVD BY NIOSH.
Ventilation:MECHANICAL(GENERAL)-SUFF TO MAINTAIN BELOW TLV LIMITS
Protective Gloves:POLYETH/NEOPREN
Eye Protection:SPLASH PROOF GOGGLES
Other Protective Equipment:ACCESSIBLE TO SAFETY SHOWER/EYE-WASH
FOUNTN,PROTECTVE CLOTHG
Supplemental Safety and Health
-*DROWS
INESS,ANESTHESIA,BLURRED VISION,EVEN DEATH,ETC.IN
CONFINED/POORYL VENTLD AREA;INGESTN:MASSIVE DOSES CAUSE NORCOTIC
ACTION & LOWER DOSES CAUSE LUNG EDEMA,LIVER & KIDNEY INJURY.

=====
===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:256F,124.5C
Vapor Pres:6.2
Vapor Density:2.62
Spec Gravity:0.966
Evaporation Rate & Reference:0.5%(N-BU ACETATE)
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR,COLORLESS LIQ W MILD AROMATIC ODOR.
Percent V

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING & CORR MATL;LONG-TERM CONTACT W AIR.

Stability Condition to Avoid:SOURCE OF IGNITION

Hazardous Decomposition Products:PROLONGED AIR CONTACT MAY FORM
EXPLOSIVE PEROXIDE

===== Disposal Considerations =====

Waste Disposal Methods:BURN WASTE LIQ IN AN APPROVED INCINERATOR IAW
EXISTING REGULATIONS.MATL ABSORBED ON A

BSORBENT MATL SHOULD BE

BURIED IN A PERMITTED HAZ WASTE MANAGEMENT FACILITY IAW LOCAL,STATE
& FED REGS/STATUTES REGARDING DISPOSAL.TREAT DAMAGED/EMPTY CONTNR
AS HAZ.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any

person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.