

ASHLAND OIL INC -- TECTYL 846 -- 8030-00-062-5866

=====  
Product Identification  
=====

Product ID:TECTYL 846

MSDS Date:01/01/1987

FSC:8030

NIIN:00-062-5866

MSDS Number: BCWTK

=== Responsible Party ===

Company Name:ASHLAND OIL INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND INC

Address:1409 WINCHESTE

R AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Phone:800-622-6846

CAGE:81355

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SOLVENTS

Fraction by Wt: 50%

ACGIH TLV:500 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:MAY CAUSE IRRIT,EXCESSIVE INHAL MAY CAUSE  
DIZZINESS,NAUSEA,VOMITTING, HDACHE.

=====  
First Aid Measures  
=====

First Aid:FLUSH EYES W/WATER,FLUSH

SKIN W/SOAP & WATER.IF  
SWALLOWED,DONOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point:105 F CC 41 C  
Lower Limits:0.8%  
Upper Limits:5%  
Extinguishing Media:CARBON DIOXIDE, FOAM, CRY CHEMICAL

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCE; STOP SPILL AT  
SOURCE,CONTAIN SPILL BY DIKE, ETC., PUMP INTO SALVAGE TANK.

===== Exposure Controls/Personal Protection

=====

Respiratory Protection:NONE REQD  
Ventilation:LOC EXHAUST-SPEC VENT AS REQD TO KP LEVELS BELOW ESTAB TLV.  
Protective Gloves:WR LONG GLOVES  
Eye Protection:SAFETY GLASSES  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:310F 154 C  
Vapor Pres:UNK  
Vapor Density:>1  
Spec Gravity: