View NSN Online: https://aerobasegroup.com/nsn/8030-00-062-6950

Product ID:PETROTECT IX,MIL-C-16173,GRADE 1 MSDS Date:01/01/1985 FSC:8030 NIIN:00-062-6950 **MSDS Number: BCWTR** === Responsible Party === Company Name: PENRECO Address:700 MILIAM ST PENNZOIL PL Box:2967 **City:HOUSTON** State:TX ZIP:77252 Country:US CAGE:PENRE === Contractor Identification === Company Name :PENRECO Address:4401 PARK AVENUE City:DICKINSON State:TX ZIP:77539 Country:US Phone:713-236-6070 CAGE:PENRE Company Name: PENRECO, DIV OF PENNZOIL CO Address:700 MILIAM ST Box:2967 City:HOUSTON State:TX ZIP:77252 Country:US Phone:800-245-3952 CAGE:86459

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:DE3030000 Fraction by Wt: 37% OSHA PEL:100 PPM

## Effects of Overexposure:EYE: BURN/IRRIT. SKIN: IRRIT. VAPORS: IRRIT,DROWSINESS,PNEUMONIA,COMA. INGESTION: IRRIT GI TRACT

First Aid:EYE: FLUSH WITH WATER 14 MIN,CALL PHYSICIAN. SKIN: WASH WITH SOAP & WATER,REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE TO FRESH AIR,GIVE ARTIF RESP IF NEEDED,CALL MD. INGESTION: DO NOT INDUCE VOMI TING,CALL A PHYSICIAN.

================= Fire Fighting Measur

Flash Point:100F/37C (PMCC) Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE Fire Fighting Procedures:TREAT AS AN OIL FIRE,WATER ONLY TO COOL EXPOSED CONTAINERS Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHEN BURNING,SOLVENT CAN CREATE MODERATE FIRE OR EXPLOSION HAZARD

Spill Release Procedures:REMOVE FROM IGNITION SOURCES,SCRAPE MATERIAL INTO WASTE CONTAINERS,OR ABSORB WITH DRY SAND OR OIL ABSORBENTS. CLEAN SPILL AREA WITH DETERGENT SOLUTIONS OR SAFETY,SOLVENTS, PROVIDE ADEQUATE VENTILATION DURING CLEAN UP.

Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM HEAT,OPEN FLAME,AND OXIDIZING MATERIALS.
Other Precautions:FIRE EXTINGUISHERS MUST BE KEPT READLY AVAILABLE & PERSONNEL TRAINED IN PROPER USE.

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN Ventilation:LOCAL/GENERAL Protective Gloves:RUBBER,SYNTHETI Eye Protection:SPLASH PROCF GOGGLES Other Protective Equipment:RUBBER PROTECTIVE CLOTHING,BOOTS,APRONS Supplemental Safety and Health 50% DISTILLATION TEMPERATURE IS BETWEEN 300-360F. PKG: 1 QT CAN. SOLVENTCONTAINS NO DETECTABLE BENZENE (IE: