View NSN Online: https://aerobasegroup.com/nsn/8040-00-065-6578

MINNESOTA MINING & MFG CO -- EC-1945A -- 8040-00-065-6578

============= Product Identification ==============

Product ID:EC-1945A MSDS Date:01/01/1985

FSC:8040

NIIN:00-065-6578

Kit Part:Y

MSDS Number: BCXBG === Responsible Party ===

Company Name: MINNESOTA MINING & MFG CO

Address:3M CTR 224-2S-25

City:ST. PAUL State:MN

ZIP:55144-1000 Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:7638

1

=== Contractor Identification ===

Company Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000 Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

======= Composition/Information on Ingredients ========

Ingred Name: AMINE EPOXY RESIN

Fraction by Wt: 3%

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 38%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200

PPM ACGIH TLV:200 PPM/300STEL;9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 33% Other REC Limits: NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:100 PPM/150STEL:9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: BUTYL ALCOHOL RTECS #:EO2000000 Fraction by Wt: 15% ========== Hazards Identification =============== Effects of Overexposure: MAY IRRIT SKIN & EYES. MAY DEFAT SKIN .POSS. SENSITIZER TO SUSCEPTBLE INDIV.SLIGHT NARCOSIS FR PRLNGED First Aid:SKIN-WASH W/SOAP & WATER. EYE CONTACT- FLUSH IMMED. W/PLENTY OF WATER, SEEK MEDICAL ATTENTION, INHALATION-PROVIDE FRESH AIR. ============ Fire Fighting Measures ========================= Flash Point:35F CC 2C Extinguishing Media:CO*2, FOAM, DRY CHEM ======== Accidental Release Measures ============ Spill Release Pro cedures:WIPE UP & DISCARD, AVOID IGNITION. ============ Handling and Storage =========================== Handling and Storage Precautions: KEEP FROM HEAT, SPARKS & FLAMES. USE IN WELL VENTILATED AREAS. AVOID PROLNGED BREATHING OF VAPORS & PROLNG OR REPTD SKN CONTCT. KEEP CONTAINER CLOSED. ===== Exposure Controls/Personal Protection ======== Ventilation:LOCAL EXHAUST Supplemental Safety and Health PROCURED UNDER 3M EC-1945A.KEY1:F3. ======= Physical/Che

HCC:F3	
Spec Gravity:8.84	
Appearance and Odor:SOLVENT ODOR	
Percent Volatiles by Volume:95	
·	

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:OXIDES OF C,H,N.

mical Properties ========

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever.

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.