

UNION CARBIDE CORP -- ARGON (HIGH PRESSURE GAS) -- 6830-00-066-1677

=====  
Product Identification  
=====

Product ID:ARGON (HIGH PRESSURE GAS)

MSDS Date:01/01/1987

FSC:6830

NIIN:00-066-1677

MSDS Number: BCXBL

=== Responsible Party ===

Company Name:UNION CARBIDE CORP

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Emergency Phone Num:304-744-3487

CAGE:36346

=== Contractor

Identification ===

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357; 304-744-3487

CAGE:36346

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ARGON

CAS:7440-37-1

RTECS #:CF2300000

Fraction by Wt: 100%

ACGIH TLV:ASPHYXIAN; 9192

=====  
Hazards Identification  
=====

Effects of Overexposure:ASPHYXIATION.

=====  
First Aid  
=====

Measures =====

First Aid:IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. KEEP WARM AND AT REST.

===== Fire Fighting Measures =====

Extinguishing Media:ARGON CANNOT CATCH FIRE. USE MEDIA APPROP. FOR SURR. AREA.

Fire Fighting Procedures:IMMEDIATELY DELUGE CONTAINERS W/ WATER UNTIL COOL.

Unusual Fire/Explosion Hazard:GAS CANNOT CATCH FIRE . CONTAINER MAY RUPTURE DUE TO HEAT OF FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL PERSONNEL FROM DANGER AREA. USE SCBA WHERE NEEDED. SHUT OFF LEAK IF WITHOUT RISK.VENTILATE AREA OF LEAK OR MOVE LEAKING CONTAINER TO WELL-VENTILATED AREA. TEST AREA FOR SUFFICIENT O\*2 BEF ORE REENTRY.

===== Handling and Storage =====

Handling and Storage Precautions:CAUTION: HIGH PRESSURE GAS. CAN CAUSE

RAPID SUFFOCATION DUE TO OXYGEN DEFICIENCY. STORE AND USWITH ADEQUATE VENTILATION.

Other Precautions:CLOSE VALVE WHEN NOT IN USE AND WHEN EMPTY. DO NOT STRIKE ARC ON CYLINDER. DO NOT GROUND CYLINDER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS WHERE NEEDED.

Ventilation:LOCAL EXHAUST PREFERRED; MECHANICAL-ADEQUATE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:METATARSEL SHOES FOR CYLINDER HANDLING.

Supplemental Safety and Health

LINDE DIVISION, 270 PARK AVENUE, NEW YORK, N.Y. 10017.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-303F,-185C

Vapor Pres:20

Vapor Density:1.38

Spec Gravity:1.38

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS, ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

INERT

===== Disposal Considerati

ons =====

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE OUTDOORS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their  
particular situation.