

WACKER SILICONE CORP -- SSILICONE FLUID SWS-101 -- 9150-00-066-2382

===== Product Identification =====

Product ID:SSILICONE FLUID SWS-101

MSDS Date:05/07/1990

FSC:9150

NIIN:00-066-2382

MSDS Number: BCXBQ

=== Responsible Party ===

Company Name:WACKER SILICONE CORP

Address:3301 SUTTON RD

City:ADRIAN

State:MI

ZIP:49221

Country:US

Info Phone Num:517-263-5711

Emergency Phone Num:517-263-5711

CAGE:4M76

8

=== Contractor Identification ===

Company Name:WACKER SILICONE CORP

Address:3301 SUTTON RD

City:ADRIAN

State:MI

ZIP:49221

Country:US

Phone:517-263-5711

CAGE:4M768

===== Composition/Information on Ingredients =====

Ingred Name:POLYDIMETHYLSILOXANE

CAS:9016-00-6

RTECS #:TQ2690000

Fraction by Wt: 100.0%

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD 50 FEMALE RAT>34,600 MG/KG

Routes of Entry: Inhalati

on:UNKNOWN Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:N/RTE:PER MSDS MATERIAL IS NONE  
TOXIC.MAY CAUSE TEMPORARY EYE IRRITATION.  
Explanation of Carcinogenicity:DATA PER MGF MSDS.  
Effects of Overexposure:MAY CAUSE TEMPORARY EYE IRRITATION.  
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE  
WORSEN.

=====  
First Aid Measures  
=====

First Aid:EYES AND SKIN:FLUSH WITH LARGE  
AMOUNT OF WATER FOR ABOUT  
15-20 MINUTES;SEEK MEDICAL ATTENTION IMMEDIATELY.INHALATION:REMOVE  
TO FRESH AIR;CALL A PHYSICIAN.INGESTION:SEEK MEDICAL ATTENTION  
IMMEDIATELY.

=====  
Fire Fighting Measures  
=====

Flash Point Method:PMCC  
Flash Point:>460F,>238C  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMI  
CAL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:NONE EXPECTED

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SCOOP UP GROSS QTY. COVER SUFACE WITH A DRY  
POWDER,BRUSH BACK & FORTH,SWEEP UP.REMOVE REMAINING DUST OR POWDER  
WITH A SAWDUST-TYPE SWEEPING COMPOUND.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL  
VENTILATED  
AREA.KEEP CONTAINER CLOSED WHEN NOT IN USE.  
Other Precautions:CLEAN UP SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NONE NORMALLY REQUIRED IF USED WITH ADEQUATE  
VENTILATION.  
Ventilation:NORMAL ROOM VENTILATION.  
Protective Gloves:AS REQUIRED  
Eye Protection:SAFETY GLASSES/GOGGLES  
Other Protective Equipment:APRON, EYE-WASH FACILITIES  
Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;D

O NOT BREATHE

VAPORS/MIST/DUST.WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

CLEAN UP SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.VISCOSITY GRADE IS  
1.0 CST.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: