

EXXON CO.USA,A DIV OF EXXON CORP. -- 1209 TURBINE LUBRICANT;P.CODE:341209-01209 --
9150-00-072-8039

===== Product Identification =====

Product ID:1209 TURBINE LUBRICANT;P.CODE:341209-01209

MSDS Date:09/10/1987

FSC:9150

NIIN:00-072-8039

MSDS Number: BCXJW

=== Responsible Party ===

Company Name:EXXON CO.USA,A DIV OF EXXON CORP.

Address:800 BELL STREET

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

C

Country:US

Info Phone Num:713-656-2443/5949

Emergency Phone Num:713-656-3424

CAGE:JO983

=== Contractor Identification ===

Company Name:EXXON CO.USA,A DIV OF EXXON CORP.

Address:800 BELL STREET

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-2443/5949

CAGE:JO983

Company Name:EXXON COMPANY U.S.A.

Address:Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

===== Composition/Information on Ingredients =====

I

ingred Name:LUBRICATING OIL BASE STOCK (64742-54-7 OR 64742-65-0)

Fraction by Wt: >95.0%

Other REC Limits:5MG/CUM AS OIL MIST

Ingred Name:TRIORTHOCRESYL PHOSPHATE

CAS:78-30-8

RTECS #:TD0350000

Fraction by Wt: 500F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM,WATER SPRAY, DRY CHEMICAL, CO*2

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:DECOMPOSITION PRODUCTS LIKE SMOKE OR FUMES, CO GAS, SULFUR-OXIDES OR ALDEHYDES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;RECOVER FREE LIQUID;USE SUITABLE ABSORBENT MATERIAL AND COLLECT FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT, OPEN FLAMES.KEEP CONTAINER CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV/PEL.

Ventilation:LOCAL EXHAUST TO MAINTAIN TLV/PEL

Protective Gloves:CHEMICAL-RESISTANT

Eye Protection:CHEMICAL GOGGLES/SIDE SHIELD

Other Protective Equipment:IMPERVIOUS CLOTHING,EYE WASH

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS/MIST;WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

MSDS RECEIVED BY DGSC:APRIL 29,1988.

=====

== Physical/Chemical Properties ==

HCC:V6

Boiling Pt:B.P. Text:555F/291C

Melt/Freeze Pt:M.P/F.P Text:14F/-10C

Vapor Pres:< 0.01 MMH

Vapor Density:> 5.0

Spec Gravity:0.88

pH:NEUTRL

Viscosity:77 CST

Evaporation Rate & Reference:< 0.01 (N-BUTYL ACETATE=1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR LIQUID,LIGHT YELLOW COLOR

Percent Volatiles by Volume:NEGLIG

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoi

d:YES

STRONG OXIDANTS

Stability Condition to Avoid:EXTREME HEAT,OPEN FLAMES

Hazardous Decomposition Products:CO GAS,SULFUR OXIDES OR ALDEHYDES

==== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH
LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States
of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.