

HYSOL DIVISION THE DEXTER CORPORATION -- R8-2038 -- 8040-00-079-7942

=====
Product Identification
=====

Product ID:R8-2038

MSDS Date:01/01/1985

FSC:8040

NIIN:00-079-7942

Kit Part:Y

MSDS Number: BCXSG

=== Responsible Party ===

Company Name:HYSOL DIVISION THE DEXTER CORPORATION

Emergency Phone Num:(716) 372-6300

CAGE:KO003

=== Contractor Identification ===

Company Name:DEXTER CORP THE DEXTER ELECTR

ONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

Company Name:HYSOL DIVISION THE DEXTER CORPORATION

CAGE:KO003

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL GLYCIDYL ETHER (BGE)

CAS:2426-08-6

RTECS #:TX4200000

Fraction by Wt: 12%.

OSHA PEL:50 PPM

ACGIH TLV:25 PPM; 9293

Ingred Name:EPOXY RESIN

=====
Hazards Identification
=====

Effects of

Overexposure:MFR STATES NO ACUTE SYMPTOMS EXPECTED.A
SENSITIZER.PROLONGED/REPEATED CONTACT MAY CAUSE SKIN RSH

=====
First Aid Measures
=====

First Aid:EYE:IMMED FLUSH W/WATER AT LEAST 15 MIN.CALL MD.SKIN:FLUSH
W/PLENTY OF WATER.WASH THOROUGHLY W/SOAP & WATER.REMOVE
CONTAMINATED CLOTHING.WASH BEFORE REUSE

=====
Fire Fighting Measures
=====

Flash Point:200F TOC
Lower Limits:0.4
Upper Limits:1.3
Extinguishing Media:SMALL FIRE:CO*2,DRY CHEM LARGE FIRE:ORDINARY FOAM
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:COVER W/ABSORBENT MATERIAL,THEN SCRAPE UP AND
TRANSFER TO METAL CONTAINER.OBSERVE FLAMMABLE CHARACTERISTICS OF
SOLVENTS,IF USED TO WIPE UP STICKY RESIDUE.ALSO TAKE PRECAUTIONS
AGAINST INHALATION HAZARD.

=====
Handling and Storage
=====

Handling and Storage Precautions:WARNING:MAY CAUSE SKIN SENSITIZATION &
OTHER ALLERGIC RESPONSES.USE ONLY W/ADEQUATE
VENTILATION,PARTICULARLY IF HEATED OR SPRAYED
Other Precautions:AVOID CONTACT W/SKIN OR EYES.PROVIDE SAFETY SHOWER &
EYE WASH.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROTECTIVE OFR PARTICLR
EXPOSURE OF CONCERN.
Ventilation:LOCAL EXHAUST-PREFERRED.MECHANICAL ACCEPTABLE.
Protective Gloves:P

LASTIC/RUBBER

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:COVERALLS OR APRON-PROTECT FROM SKIN &
CLOTHING

Supplemental Safety and Health

BP GIVEN @ 95 MMHG.VAPOR DENSITY GIVEN @ 25C.PART A OF A TWO PART
PRODUCT.PART B IS HD-3475,SEE SAME NSN,P/N INDICATOR B.MIX RATION
(BY WEIGHT) PART A/PART B IS 100/25.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:284F

Vapor Pres:2.

Vapor Density:3.8

Spec Gravity:1.14

Evapora

tion Rate & Reference:>1 BUTYL ACETATE

Solubility in Water: