

THREE BOND OF AMERICA, INC -- GRADE B,YELLOW -- 8030-00-081-2335  
===== Product Identification =====

Product ID:GRADE B,YELLOW

MSDS Date:01/01/1987

FSC:8030

NIIN:00-081-2335

MSDS Number: BCXWJ

=== Responsible Party ===

Company Name:THREE BOND OF AMERICA, INC

Emergency Phone Num:213-556-3614

CAGE:DO698

=== Contractor Identification ===

Company Name:MILITARY SPECIFICATIONS PROMULGATED BY MILITARY  
Ad

dress:DEPTS/AGENCIES UNDER AUTH OF DEF STD

Box:MANUAL

City:4120 3-M

Phone:804-279-4371 DSN 695-4371

CAGE:81349

Company Name:THREE BOND OF AMERICA, INC

Address:20815 HIGGINS COURT

Box:City:TORRANCE

State:CA

ZIP:90501

Phone:800-424-9300 CHEMTREC

CAGE:DO698

===== Composition/Information on Ingredients =====

Ingred Name:EPOXYLATED BISPHENOL DIMETHACRYLATE

Fraction by Wt: 76%

Ingred Name:ALIPHATIC ESTER PLASTICIZER

Fraction by Wt: 9%

Ingred Name:TERTIARYAMINE

Ingred Name:CATALY

ST

Ingred Name:METHACRYLATE ESTER

===== Hazards Identification =====

Effects of Overexposure:EYE & SKIN IRRITANT.EFFECT CAN BE  
DELAYED.POTENTIAL SKIN SENITIZER.SLIGHTLY TOXIC(ACUTE ORAL TOXICIT

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT,FLUSH SKIN W/PLENTY OF WATER;FOR  
EYES,FLUSH W/WATER FOR AT LEAST 15 MINUTES & SEEK MEDICAL  
ATTENTION.WASH CONTAMINATED CLOTHING BEFORE RE-USE (DISCARD  
CO  
NTAMINATED SHOES)

===== Fire Fighting Measures =====

Flash Point:>200F >93C  
Extinguishing Media:FOAM,CARBONDIOXIDE OR DRY CHEMICAL,WATER SPRAY  
Fire Fighting Procedures:EVACUATE AREA OF ALL NON-EMERGENCY  
PERSONNEL.FIRE FIGHTERS M  
Unusual Fire/Explosion Hazard:RAPID & VIOLENT PROLYMERIZATION MAY OCCUR  
AT ELEVATED TEMPERATURES;HENCE,CONTAINERS MUST BE COOLED W

===== Accidental Release Measures =====

Spill Release Procedures:A  
VOID EYE OR SKIN CONTACT OR ORAL  
INGESTION.WEAR PROTECTIVE EQUIPMENT AS DESCRIBED IN SECTION VIII  
BELOW.WASH AREA THOROUGHLY & COLLECT MATERIAL FOR INCINERATION.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL PLACE IN ORIG  
CONTNR;KEEP OUT OF DIRECT SUNLIGHT.EMPLOYER SHD PROVIDE CHG OF  
CLOTH & SHOES TO BE AIRED DAILY & WASHED FREQ(SEE OTHER PRE  
Other Precautions:DISCARD ITEMS IF CONTAMINATED BY SPILL.AT END OF

SHIFT BEFORE CHANGING CLOTHES,WORKER SHOULD TAKE HOT-NOT COLD SHOWER TO REMOVE TRACE OF VAPORS IN PORES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL VENTILATION REQUIRED  
Ventilation:LOCAL EXHAUST PREFERRED.MECH(GEN),NORMAL VENTILATION  
AGEQUAT  
Protective Gloves:IMPERVIOUS GLOV  
Eye Protection:CHEMICAL SAFETY GOGGLES  
Other Protective Equipment:IMPERVIOUS OVERSHOES & PROTECTIVE CLOTHING  
Supplemental Safety and Health  
BOILING RANG  
E:ESTIMATED @760MMHG>60000F

===== Physical/Chemical Properties =====

HCC:N1  
Boiling Pt:B.P. Text:EST @760MMH  
Vapor Density:HEAV  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:0.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO  
PEROXIDES OR OTHER STRONG OXIDIZING AGENTS,IRON RUST,STRONG  
Stability Condition to Avoid:TEMP.ABOVE 90F,PROLONGED EXPOSURE TO  
LIGHT,OPEN FLAME,  
METH  
Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:CHEMICAL INCINERATOR.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use.

Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.