

CORONADO PAINT CO, INC. -- COATING, EPOXY, WHITE -- 8010-00-082-2440

=====
Product Identification
=====

Product ID:COATING, EPOXY, WHITE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-082-2440

Kit Part:Y

MSDS Number: BCXYM

=== Responsible Party ===

Company Name:CORONADO PAINT CO, INC.

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

CAGE:33200

=== Contractor Identificati

on ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYAMIDE RESIN

Fraction by Wt: 28.6%

ACGIH TLV:NO HAZARD

Ingred Name:EPOXY RESIN

Fraction by Wt: 10.7%

ACGIH TLV:500PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 8.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SOLVENTS, (ESTERS, ALCOHOLS)
Fraction by Wt: 43.2%
ACGIH TLV:500PPM

===== Hazards Identification =====

Effects of Overexposure:PRODUCES SEVERE EYE IRRITATION, DRYING OF SKIN.
EXCESSIVE INHALATION: HEADACHE, DIZZINESS, NAUSEA.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH MILD SOAP AND WATER
AND APPLY SKIN CREAM. INHALATION:
REMOVE TO FRESH AIR AND CALL
PHYSICIAN. APPLY ARTIFICIAL RESPIRATION, IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point:45F SETA
Lower Limits:1
Upper Limits:7
Extinguishing Media:DRY CHEMICAL, FOAM, CO2
Fire Fighting Procedures:TREAT AS A CLASS B FIRE.
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURES WITH
AIR.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER INTO
RETAINING AREA OR
CONTAINER. AVOID EXPOSURE TO SPARKS, FIRES, HOT METAL SURFACES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN
FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR PEATED
SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR IF TLV IS EXCEEDED
Ventilation:LOCAL EXHAUST
Protective Gloves:YES

Eye Protection: YES
Other Protective Equipment: EYE BATH AND SAFETY SHOWER
Supplemental Safety and Health
308 OLD COUNTY RD. EDGEWATER, FLA 32032.

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 230F
Vapor Pres: 23
Vapor Density: 3.2
Spec Gravity: 1.325
Evaporation Rate & Reference: 1.3, NBUAC=1
Solubility in Water: NEGLIGIBLE
Appearance and Odor: AROMATIC ODOR; WHITE OPAQUE LIQUID, WHEN MIXED.
Percent Volatiles by Volume: 60

===== Stability
and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZERS
Stability Condition to Avoid: EXCESSIVE HEAT, SPARKS, OPEN FLAME
Hazardous Decomposition Products: THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: LANDFILL OR INCINERATION UNDER SAFE SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.