

ZEBRA CORPORATION -- TT-P-85D PAINT TRAFFIC -- 8010-00-082-2598

=====
Product Identification
=====

Product ID:TT-P-85D PAINT TRAFFIC

MSDS Date:01/01/1985

FSC:8010

NIIN:00-082-2598

MSDS Number: BCYBN

=== Responsible Party ===

Company Name:ZEBRA CORPORATION

Country:US

Emergency Phone Num:404 873-2531

CAGE:KO023

=== Contractor Identification ===

Company Name:ZEBRA CORPORATION

Country:US

CAGE:KO023

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 38.1%

ACGIH TLV:275 PPM

Ingred Name:VEHICLE

Fraction by Wt: 21.0%

Ingred Name:PIGMENTS

Fraction by Wt: 50.9%

=====
Hazards Identification
=====

Effects of Overexposure:DRYING OF SKIN. EYE IRRITATION. EXCESSIVE
INHALATION MAY CAUSE HEADACHE, DIZZINESS, NAUSEA.

=====
First Aid Measures
=====

First Aid:INHALATION

: REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION
IF NECESSARY, CALL A PHYSICIAN. SKIN CONTACT: WASH WITH MILD SOAP
AN WATER, APPLY A MILD SKIN CREAM, IN SEVERE CASES CONTACT A
PHYSICIAN. EYE CONTACT: FLUSH WITH WATER.

=====
===== Fire Fighting Measures =====

Flash Point:50F TCC
Lower Limits:0.9
Upper Limits:6
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER SPRAY
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion
Hazard:WATER MAY BE UNSUITABLE EXCEPT AS A
COOLING MEDIUM.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER INTO RETAINING AREA OR
CONTAINER. AVOID SPARKS, FIRE OR HOT METAL SFACES. SMALL QUANTITIES
MAY BE ABSORBED ONTO AN APPROPRIATE ABSORBANT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL AND AWAY FROM SOURCES OF
IGNITION. USE WITH ADEQUATE VENTILAT
ION. AVOID PROLONGED OREPEATED
PERSONAL CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:CARTRIDGE RESPIRATOR OR GAS MASK
Ventilation:LOCAL EXHAUST: WHATEVER IS SUFFICIENT TO KEEP WORKROOM
Protective Gloves:IMPERMEABLE
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:APRON, BARRIER CREAM
Supplemental Safety and Health
ZEBRA CORPORATION 698 ECHO STREET ALTANTA, GEORGIA 30318

=====
===== Physical/Chemical Properties =====

=====

HCC:F2

Boiling Pt:B.P. Text:250-300

Vapor Pres:68F

Vapor Density:4.1

Spec Gravity:1.42

Evaporation Rate & Reference:1.0

Solubility in Water:NEGLIGIBLE

Appearance and Odor:OPAQUE LIQUID-MILD PETROLEUM AROMA

Percent Volatiles by Volume:45.2

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME FIRE

Hazardous Decomposition Products:THERMAL DECOM

POSITION MAY YIELD CARBON

MONOXIDE AND DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF
IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, wa

rrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.