

GENERAL ELECTRIC CO,SILICONE PRODUCTS BUSINES DEPT -- F50;LUBRICATING OIL --
9150-00-082-5636

===== Product Identification =====

Product ID:F50;LUBRICATING OIL

MSDS Date:08/05/1988

FSC:9150

NIIN:00-082-5636

MSDS Number: BCYCJ

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO,SILICONE PRODUCTS BUSINES DEPT

Address:HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone N

um:518-237-3330

Emergency Phone Num:518-237-3330

Preparer's Name:DA POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:CHLOROPHENYLMETHYLPOLYSILOXANE

Ingred Name:OTHER COMPONENTS (NOT SPECIFIED)

===== Hazard

s Identification =====

Health Hazards Acute and Chronic:ACUTE:MILD IRRITATION OF EYES AND SKIN; NO OTHER INFORMATION HAS BEEN GIVEN. CHRONIC:NO DATA AVAILABLE.

Effects of Overexposure:MILD IRRITATION OF EYES AND SKIN.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

===== First Aid Measures =====

First Aid:EYES AND SKIN:FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINUTES;SEEK MEDICAL ATTENTION IF NEEDED.

=====

== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>550F/287C

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:NONE NOTED.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;WIPE,SCRAP OR SOAK UP IN AN INERT MATERIAL AND COLLECT FOR PROPER DISPOSAL;WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE SLIPPING HAZARDS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED IF THERE IS AN ADEQUATE VENTILATION.

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:IMPERVIOUS.

Eye Protection:SAFETY GLASSES.

Other

Protective Equipment:APRON,EYE-WASH STATION.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;KEEP GOOD
HYGIENE PRACTICES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V5

Boiling Pt:B.P. Text:>500F/260C

Vapor Pres:1.0 MMHG

Spec Gravity:1.025

pH:NEUTRL

Evaporation Rate & Reference:>1.0 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER ODORLESS LIQUID.

Percent Volatiles by Volume: