

AMERON PROTECTIVE COATINGS -- WHITE 27875 -- 8010-00-087-0107

=====
Product Identification
=====

Product ID:WHITE 27875

MSDS Date:01/01/1987

FSC:8010

NIIN:00-087-0107

MSDS Number: BCYHJ

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

City:BREA

State:CA

ZIP:92622-1020

Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2E4

=== Contractor Identification ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

=====
Composition/Information on Ingredients
=====

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 36%

Other REC Limits:STEL 400 PPM

OSHA PEL:100 PPM

ACGIH TLV:300 PPM

Ingred Name:LEAD CHROMATE, LEAD CHROMIUM OXIDE (SUSPECTED

HUMAN

CARCINOGEN BY ACGIH, IARC-GRP 1; NTP) *97-3*

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 0.24%

OSHA PEL:0.1 MG/CUM (CRO3)

ACGIH TLV:0.05 MG/CUM (PB)

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. IRRITATION OF
RESPIRATORY TRACT & MAY CAUSE NERVOUS SYSTEM DEPRESSION. SKIN/EYES:
IRRITA
TION.

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:IRRITATION

=====
First Aid Measures
=====

First Aid:SKIN/EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR.
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:85F

Lower Limits:1.1

Extinguishing Media:SMALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: FOAM

Fire Fighting Procedures:USE SEL

F CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION; HOT SURFACES,
ELECTRICAL STATIC/FRICTIONAL SPARKS. AVOID BREATHING VAPORS. REMOVE
W/INERT ABSORBENT & NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. ST

ORE LARGE

QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE
FLAMMABLE/COMBUSTIBLE.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR/AIR SUPPLIED
RESPIRATOR. RESPIRATOR USED BASED ON CHEMICAL CONDITION &
CONDITIONS OF USE.

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST
AS NECESSARY.

Protective Gloves:REQUIRED

Eye Protection:REQUIRED

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Pres:3

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:57

===== Stability and Reactivity Data =====

Stability Indicator/Materials to A

void:YES

Stability Condition to Avoid:FIRE, HEAT, HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL
REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants t

his information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.