View NSN Online: https://aerobasegroup.com/nsn/6850-00-105-3084

Product ID:MIL-C-81302C ;CLEANING CMPD SOLVENT;TYIIA MSDS Date:01/01/1987 FSC:6850 NIIN:00-105-3084 **MSDS Number: BCYTT** === Responsible Party === Company Name: BULK CHEMICAL DIST. INC. Emergency Phone Num:504-362-3232 CAGE:EO174 === Contractor Identification === Company Name:BU LK CHEMICAL DIV, MALTER INTERNATIONAL Address:80 FIRST ST **City:GRETNA** State:LA ZIP:70053 Country:US CAGE:EO174 Company Name: BULK CHEMICALS DISTRIBUTORS, INC Address:80 FIRST STREET City:GRETNA, State:LA ZIP:70053 Country:US Phone:504-362-3232 DISCONNECTED(2-20-92) CAGE:56921 Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III) CAS:76-13-1 RTECS #:KJ4000000 Fraction by Wt: 75% OSHA PEL:1000PPM/1250STEL А

CGIH TLV:1000PPM/1250STEL9192 Ozone Depleting Chemical:1
Ingred Name:PROPELLANT(TYPE NOT SPECIFIED) Fraction by Wt: 25%
======================================
Effects of Overexposure:MAY IRRITATE EYES,THROAT AND SKIN;EXCITEMENT;IN COORDINATION,TREMORS IN RATS.
======================================
First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GE
T MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.
======================================
Flash Point:N/R AEROSOL Extinguishing Media:N/R USE MEDIA SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SCBA. KEEP CONTAINERS COOL W/WATER. Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST AT TEMP ABOVE 120F. TOXIC GAS MAY BE LIBERATED.
======================================
Spill Rele ase Procedures:EVACUATE AND VENTILATE AREA. ALLOW TO EVAPORATE NORMALLY.
======================================
<ul> <li>Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT AREA AWAY FROM HEAT SOURCES,OPEN FLAME.</li> <li>Other Precautions:MATL DISPLACES OXYGEN AND MAY RESULT IN SUFFOCATION IF USED IN NON-VENT CLOSED AREAS. KEEP OUT OF REACH OF CHILDREN.</li> </ul>
======================================

Respiratory Protection:NO SPECIAL REQMN

TS UNDER ORDINARY CONDITIONS/ADEQUATE VENT. Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION Protective Gloves:IMPERVIOUS Eye Protection:CHEM SPLASH GOGGLES Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT. Supplemental Safety and Health MSDS UNDATED;ITEM IS OF CLASS 2 AND TYPE IIA.

HCC:V2

Boiling Pt:B.P. Text:118F/48C Vapor Density:6.5 Spec Gravity:1.565 Evaporation Rate &am p; Reference:1.69 (CARB-TET=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:CLOLORLESS WITH ETHEREAL ODOR WITH PROPELLANT. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES CHEM ACT METALS;CALCIUM,PWD ALUMINUM,ZINC, MAGNESIUM Stability Condition to Avoid:TEMPERATURES ABOVE 250F. Hazardous Decomposition Products:HALOGENS & CARBONYL HALIDES

======== Disposal Considerations =========

\_\_\_\_\_

Waste Disposal Methods:DO NOT INCINERATE CANS. MATL MAY BE RECALIMED BY AUTHORIZED FAC. DISPOSE I/A/W LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.