

CSD INC. (OBSOLETE ADDRESS; USE 4N760) -- DRY CLEANING SOLVENT -- 6850-00-110-4498

=====  
Product Identification  
=====

Product ID: DRY CLEANING SOLVENT

MSDS Date: 08/27/1986

FSC: 6850

NIIN: 00-110-4498

MSDS Number: BCYYN

=== Responsible Party ===

Company Name: CSD INC. (OBSOLETE ADDRESS; USE 4N760)

Address: 420 SEABOARD DRIVE

City: MATTHEWS

State: NC

ZIP: 28105-5073

Country: US

Info Phone Num: 704-821-9822

E

Emergency Phone Num: 704-821-9822

Preparer's Name: ILLEGIBLE SIGNATURE

CAGE: 5W216

=== Contractor Identification ===

Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address: 2210 HACKBERRY LN

Box: 687

City: CONROE

State: TX

ZIP: 77305

Country: US

Phone: 409-756-1065

CAGE: 4N760

Company Name: CSD INC. (PRE 1985 NAME: MATHEWS, INC)

Address: 420 SEABOARD DRIVE

Box: City: MATTHEWS

State: NC

ZIP: 28105-5073

Country: US

Phone: 704-821-9822

CAGE: 5W216

=====  
Composition/Information on Ingredients  
=====

====

Ingred Name:SOLVENT 140  
Other REC Limits:37PPM  
OSHA PEL:100PPM(STODDARD SOL)  
ACGIH TLV:100PPM(STODDARD SOL)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF  
OVEREXPOSURE.  
Explanation of Carcinogenicity:MANUFACTURER DID NOT SPECIFY.  
Effects of  
Overexposure:EYES:IRRITATION;SKIN:DRYNESS,DEFATTING,IRRITATION,DERM  
ATITIS;INHALATION:DIZZINESS,HEADACHE,UNCONSCIOUSNESS;INGESTION:MANU  
FACTURER DID NOT SPECIFY SYMPTOMS.  
Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS.SKIN  
CONDITION.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER UNTIL IRRITATION  
SUBSIDES;SKIN:REMOVE CONTAMINATED CLOTH AND SHOES,AND WASH WITH  
SOAP AND WATER;INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF  
NEEDED;INGESTION:DO NOT INDUCE VOMIT.SEE DOCTOR.

===== Fire  
Fighting Measures =====

Flash Point Method:TCC  
Flash Point:142F(61C)  
Lower Limits:0.9  
Upper Limits:6.0  
Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2,WATER FOG OR SPRAY.  
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR  
ENCLOSED AREAS.COOL EXPOSED CONTAINERS WITH WATER SPRAY.AVOID  
BREATHING VAPORS OR FUMES.  
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE I

IGNITION SOURCES. VENTILATE. OPEN ALL  
WINDOWS AND DOORS. AVOID BREATHING VAPORS. WEAR RESPIRATOR. ABSORB IN  
INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINERS CLOSED. DO NOT STORE  
NEAR HEAT, SPARKS, FLAMES OR STRONG OXIDANTS. ADEQUATE VENTILATION IS  
REQUIRED.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE HYDROCARB  
ON VAPOR CANISTER OR SUPPLIED AIR

RESPIRATOR IN CONFINED SPACES IF NEEDED.

Ventilation: LOCAL EXHAUST. FACE VELOCITY > 60 FPM. USE EXPLOSION PROOF  
EQUIPMENT. NO SMOKING OR OPEN LIGHTS.

Protective Gloves: CHEMICAL RESISTANT: PVA.

Eye Protection: SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment: PVA APRON OR OTHER CHEMICAL RESISTANT APRON.

Work Hygienic Practices: AVOID BREATHING VAPORS. AVOID SKIN

CONTACT. REMOVE CONTAMINATED CLOTH & SHOES. LAUNDRY CLOTH. THOROUGHLY  
DRY SHOES.

Supplem

ental Safety and Health

WASH SKIN THOROUGHLY WITH SOAP AND WATER AFTER CONTACT.

=====  
===== Physical/Chemical Properties =====

HCC: V4

Boiling Pt: B.P. Text: 367F (186C)

Vapor Pres: