

GULF OIL CHEMICALS CO. -- SYNFLUID TS-803 -- 9150-00-111-6256

=====
Product Identification
=====

Product ID:SYNFLUID TS-803

MSDS Date:01/01/1985

FSC:9150

NIIN:00-111-6256

MSDS Number: BCZDB

=== Responsible Party ===

Company Name:GULF OIL CHEMICALS CO.

Emergency Phone Num:(713) 651-0693

CAGE:2U019

=== Contractor Identification ===

Company Name:GULF OIL CHEMICALS CO PETROCHEMICALS DIV

Address:FANNI

ON ST AND MCKINNEY ST

Box:3766

City:HOUSTON

State:TX

ZIP:77001

Country:US

Phone:713-651-0693

CAGE:2U019

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYALPHAOLEFIN

=====
Hazards Identification
=====

Effects of Overexposure:PRLNG/RPTD SKIN CNTCT MAY CAUSE MOD IRRIT.
PRLNG EXPOS TO MIST/FUME MAY IRRIT EYES, NOSE, MUC MEMBRN

=====
First Aid Measures
=====

First Aid:SKIN: REMOVE BY

WIPING & WASH W/ SOAP & WATER. EYE: WASH

W/COPIOUS AMTS OF WATER. INH: REMOVE FROM EXPOS. INGEST: DO NOT
INDUCE VOMITING(ASPIRATION HAZARD). GIVE 2-4 OZ. OLIVE OR VEGETABLE
OIL & 1-2 O Z. ACTIVATED CHARCOAL. SEEK MEDICAL AID.

=====
Fire Fighting Measures
=====

Flash Point:420F CC

Extinguishing Media:CO*2, DRY CHEMICAL

Fire Fighting Procedures:USE WATER TO COOL EXPOS CANS. USE FOAM/WATER
SPRY FOR FROTHG

Unusual Fire/Explosion Hazard:SLIGHT WHEN

EXPOSED TO HEAT OR FLAME; CAN
REACT W/ OXIDIZING MATERIALS. COMBUST AT HIGH TEMP.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW, ELIM ALL SOURCES OF IGNIT. AVOID
DERMAL CONTACT, USE SKIN PROTECTION. ABSORB OR SCRAPE UP. REMOVE
SOILED CLOTHING. OBSERVE GOVERNMENTAL SPILL & WATER QUALITY
REGULATIONS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID FREQUENT OR PROL
ONGED SKIN

CONTACT OR INH OF FUMES, MISTS, VAPORS. HANDLE & STORE USING
METHODS GEN ADVOCATED FOR COMBUSTIBLE HYDROCARBONS

Other Precautions:DO NOT WEAR OIL-SOILED CLOTHING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RSP (SEE SUPP)

Ventilation:GENERAL & LOCAL EXHAUST IF FUMES EXCEED TLV, SPECIAL AS
REQD

Protective Gloves:BUTYL RUBBER

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:OIL-IMPERV OR PROTECT GAR
MENTS. POLYVINYL

ALCHL GLOVES ACCPT

Supplemental Safety and Health

OVERPOINT: (OIL BASE) 374-384F. VAPOR PRESSURE: NEGLIGIBLE. RESP PROT:

MAY ALSO USE NIOSH/MSHA APPVD FULL FACE MASK POSITIVE

PRESSURE-DEMAND IF NEC. POLYETHYLENE GLOVES ARE ALSO ACCEPTABLE.

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.8438

Evaporation Rate & Reference:0

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, PALE LUBRICATING OIL

Percent Volatiles b

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

MAY REACT W/OXIDIZING MATERIAL

Hazardous Decomposition Products: HEATED TO DECOMP POSS SM QTY FREE

PHENOL, POSS SKIN/EYE IRRIT

===== Disposal Considerations =====

Waste Disposal Methods: MFR RECM INCINERATE UNDER CONTROLLED CONDITIONS.

DISPOSE IAW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.