View NSN Online: https://aerobasegroup.com/nsn/8010-00-138-1760

DEFT,INC -- 03Y31CAT, YELLOW, 13655 -- 8010-00-138-1760

Product ID:03Y31CAT, YELLOW, 13655

MSDS Date:01/01/1987

FSC:8010

NIIN:00-138-1760

Kit Part:Y

MSDS Number: BDBHT === Responsible Party === Company Name: DEFT, INC

Address:17451 VON KARMAN AVE

City:IRVINE State:CA

ZIP:92714-6205

Country:US CAGE:KO193

=== Contractor Identification === Company Name: DEFT, INC.

Ad

dress:17451 VON KARMAN AVE

City:IRVINE State:CA ZIP:92614 Country:US

Phone:949-474-0400

CAGE:33461

Company Name: DEFT, INC

Address:17451 VON KARMAN AVE

City:IRVINE State:CA

ZIP:92714-6205 Country:US CAGE:KO193

======= Composition/Information on Ingredients ========

Ingred Name: CELLOSOLVE ACETATE

RTECS #:FJ4375000 Fraction by Wt: 10% ACGIH TLV:5PPM

Ingred Name:BIURET OF 1.6 HEXAMETHYLENE DIISOCYANATE

Fraction by Wt: 30% ACGIH TLV:0.02PPM

Ingred Name: N-BUTYL ACETATE

RTECS #:EO072000

Fraction by Wt: 5% ACGIH TLV:150PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 5%

OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 45%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/300STEL;9394

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Hazards Identification ==========

Effects of

Overexposure:IHALATION:HEADACHE,DIZZINESS,UNCONSCIOUSNESS.EYE AND SKIN IRRITATION.ALLERGIC SENSITIVITY.

First Aid:INHALATION:REMOVE FROM EXPOSURE;KEEP WARM AND QUIET.NOTIFY A PHYSICIAN.EYES:15 MINUTE WATER FLUSH.SKIN:REMOVE CONTAMINATED CLOTHING.WASH SKIN WITH WATER.

Flash Point:24F

,-4C TCC

Lower Limits: 1.0


Extinguishing Media:FOAM,CO*2,DRY CHEMICAL,WATER FOG

Fire Fighting Procedures: SELF CONTAINED BREATHING APPAR. WATER FOG TO COOL CONTAINERS.

Unusual Fire/Explosion Hazard:ISOLATE FROM SOURCES OF IGNITION, EXTREME HEAT.KEEP CONTAINERS TIGHTLY CLOSED.HOT SURFACES CAUTION

======== Accidental Release Measures =============

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.AVOID BREATHING VAPOR.CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON



-SPARKING

Waste Disposal Methods: IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INC

INERATE IN APPROVED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.