

REGAL AIR CORP -- RR 990,RAIN REPELLANT,WINDSHIELD -- 6850-00-139-5297

=====  
Product Identification  
=====

Product ID:RR 990,RAIN REPELLANT,WINDSHIELD

MSDS Date:03/10/1989

FSC:6850

NIIN:00-139-5297

MSDS Number: BDBLJ

=== Responsible Party ===

Company Name:REGAL AIR CORP

Address:568 MYRTLE AVE

City:BOONTON

State:NJ

ZIP:07005

Country:US

Info Phone Num:201-366-3294

Emergency Phone Num:201-366-3294

CA

GE:98511

=== Contractor Identification ===

Company Name:REGAL AIR CORP

Address:568 MYRTLE AVE

Box:City:BOONTON

State:NJ

ZIP:07005

Country:US

CAGE:98511

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:SILICON DERIVATIVE (PRORIETARY)

CAS:7440-21-3

RTECS #:VW0400000

Other REC Limits:NONE SPECIFIED

OSHA PEL

:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PRODUCT IS SLIGHTLY CORROSIVE TO HUMAN  
TISSUE, SKIN, AND EYES.  
Explanation of Carcinogenicity:MFR MAKES NO STATEMENT. HMIS EXPECTS NO  
CARCINOGENITY.  
Effects of Overexposure:MILD IRRITATION OF EYES, NOSE, THROAT.  
FORMULATION MAY INVOLVE MILD NARCOSSIS.  
Medical Cond Aggravated by Exposure:NOT DETERMINED.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION  
PERSISTS GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED  
CLOTHING. WASH AREA WITH SOAP AND WATER. INHALATION: MOVE TO FRESH  
AIR. INGESTION: GIV E MILK OR WATER. GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:OC  
Flash Point:53.0F,11.7C  
Lower Limits:2  
Upper Limits:12  
Extinguishing Media:CARBON DIOXIDE, SAND, FOAM, DRY CHEMICAL.  
Fire Fighting Procedures:USE WATER TO COOL CONTAINERS EXPOSED TO FIRE.  
USE SCBA AND FULL PROTECTIVE CLOTHING WHEN FIGHTING FIRES INCLUDING  
CHEMICALS.  
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION

SOURCES. COVER SPILL WITH  
ABSORBENT MATERIAL SUCH AS SAWDUST OR SAND. SCOOP UP AND PLACE IN  
SUITABLE CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL, DRY AREA AWAY FROM FOOD  
AND BEVERAGES. PRODUCT IS FLAMMABLE. KEEP SEALED. PROTECT FROM  
MOISTURE AND PHYSICAL DAMAGE.

Other Precautions:IF TRANSFERRING TO METAL CONTAINERS, MAKE SURE  
CON  
TAINERS ARE GROUNDED ELECTROSTATICALLY.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH RESPIRATOR WITH ORGANIC VAPOR  
CARTRIDGE IF TLV IS EXCEEDED.

Ventilation:SHOULD NOT BE NEEDED UNDER NORMAL USEAGE. USE LOCAL EXHAUST  
WHERE NECESSARY TO MAINTAIN EXPOSURE BELOW THE TLV.

Protective Gloves:RUBBER/PLASTIC

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED SKIN  
CONTACT.

Work Hygienic Practices:

WASH AFTER HANDLING AND BEFORE EATING,  
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:F2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:=80.C, 176.F

Vapor Density:>1

Spec Gravity:0.80-0.82

Evaporation Rate & Reference: