View NSN Online: https://aerobasegroup.com/nsn/8010-00-141-7838

ARROW PAINT & VARNISH CO. -- LR-7132C OLIVE DRAB WW TYPE II 34087 -- 5610-00-141-7838

Product ID:LR-7132C OLIVE DRAB WW TYPE II 34087

MSDS Date:01/01/1987

FSC:5610

NIIN:00-141-7838

MSDS Number: BDBQH === Responsible Party ===

Company Name: ARROW PAINT & VARNISH CO.

Address: 1390 FIRESTONE PARKWAY

City:AKRON State:OH

ZIP:44301-1624 Country:US CAGE:KO224

=== Contrac

tor Identification ===

Company Name: AKRON PAINT AND VARNISH INC

Address: 1390 FIRESTONE PARKWAY

City:AKRON State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

Company Name: ARROW PAINT & VARNISH CO.

Address:1390 FIRESTONE PARKWAY

Box:City:AKRON

State:OH

ZIP:44301-1624 Country:US CAGE:KO224

======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000 Fraction by Wt: 0.4% OSHA PEL:100 PPM

Ingred

Name: N-BUTYL ACETATE (SARA III) CAS:123-86-4 RTECS #:AF7350000 Fraction by Wt: 23% Other REC Limits: NONE RECOMMENDED **OSHA PEL:150 PPM** ACGIH TLV:150 PPM/200STEL;9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 5.6% Other REC Limits: NONE RECOMMENDED OSHA PEL:200 PPM; Z-2 ACGIH TLV:S, 50 PPM; 9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 40.9% OSHA PEL:100 PPM Ingred Name: BUTYRALDEHYDE OXIME CAS:110-69-0 RTECS #:ES3500000 Fraction by Wt: 0.5% ========= Hazards Identification =============== Effects of Overexposure:PROLONGED OR REPEATED EXPOSURE MAY CAUSE NAUSEA, HEADACHE AND LOSS OF CONSCIOUSNESS; NARCOSSIS AND IRR

First Aid:SKIN CONTACT:WASH CAREFULLY W/MINERAL SPIRITS, THEN W/SOAP AND WATER, EYE CONTACT: FLUSH PROM

MEDICAL ATTENTION.INHALATION: REMOVE INDIVIDUAL TO FRESH AIR AND USE OXY GEN IF NECESSARY. OBTAIN MEDICAL ATTENTION. Flash Point: 40 F CC 4 C TOL Extinguishing Media: CARBON DIOXIDE, FOAM OR DRY CHEMICAL Fire Fighting Procedures: WATER SPRAY TO COOL CONTAINRS. WEAR **SELF-CONTAINED BREATHIN** Unusual Fire/Explosion Hazard: HEAT MAY CAUSE DISRUPTIVE PRESSURE OF CONTAINERS, AND FLAMMABL E VAPORS MAY FORM EXPLOSIVE MIXT ======== Accidental Release Measures ============ Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION DAM UP TO LIMIT SPREADING.ABSORB ON INERT MATERIAL. VENTILATE AREA. =========== Handling and Storage ============================ Handling and Storage Precautions: DO NOT DROP CONTAINERS. AVOID HEAT, SPARKS AND OPEN FLAME, STORE AT ROOM TEMP W/GOOD VENTILATION. Other Precautions: CONTAINS LEAD AND/OR CHROMATE PIGMENTS.IF SUBJECT SPRAY APPLICATION, ENGINEERING AND ADMINISTRATIVE. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: USE APPROPRIATE BUREAU OF MINES APPROVED RESPIRATOR WHEN SPRAYING OR Ventilation: PROVIDE ADEQUATE VENTILATION AND EXPLOSION-PROOF EQUIPMENT. Protective Gloves: CHEMICAL RESIST Eye Protection: SAFETY GOGGLES W/SIDE SH Other Protective Equipment: NORMAL PROTECTIVE CLOTHING. Supplemental Safety and Health FLASH POINT 40 F CC (4.C) IS FOR TOLUOL ======== Physical/Chemical Properties ================ HCC:F2 Boiling Pt:B.P. Text:TOLUOL 231 Evaporation Rate & Evaporation R Percent Volatiles by Volume:69.5 ========= Stability and Reactivity Data ============== Stability Indicator/Materials to Avoid:YES **AVOID OXIDIZING AGENTS** Hazardous Decomposition Products: COMBUTION IN RESTRICTED ENVIRONMENT CAN PRODUCE CARBON M ======= Disposal Considerations =========== Waste Disp

PLTY AND THOROUGHLY W/WATER AND OBTAIN

osal Methods:DISPOSE IN ACCORDANCE W/APPLICABLE POLLUTION CONTROL REGULATIONS.DO NOT INCINERATE CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.