

EVERSEAL MFG CO, INC -- WALKWAY COMPOUND TYPE II BLACK 37038 -- 5610-00-142-6525
===== Product Identification =====

Product ID:WALKWAY COMPOUND TYPE II BLACK 37038

MSDS Date:01/01/1987

FSC:5610

NIIN:00-142-6525

MSDS Number: BDBQW

=== Responsible Party ===

Company Name:EVERSEAL MFG CO, INC/RIDGEFIELD, NJ 07657

Emergency Phone Num:(201) 943-4986

CAGE:DO261

=== Contractor Identification ===

Company

Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGEFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

Company Name:EVERSEAL MFG CO, INC

Address:475 BROAD AVE

City:RIDGEFIELD

State:NJ

ZIP:07657

Phone:201-943-4986

CAGE:DO261

===== Composition/Information on Ingredients =====

Ingred Name:RESIN (SEE SUPPLEMENTAL FOR INGREDIENTS)

Fraction by Wt: 21%

Ingred Name:SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN
1% CRYSTALLINE SILICA

CAS:

61790-53-2
RTECS #:HL8600000
Fraction by Wt: 7%
OSHA PEL:20 MPPCF
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 2.0%
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 32%
OSHA PEL:100 PPM

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 27%
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

=====
===== Hazards Identification =====

Effects of Overexposure:ANESTHESIA-HEADACHE, NAUSEA, DIZZINESS. LIQUID
SLIGHTLY IRRITATING TO SKIN & EYES.

===== First Aid Measures =====

First Aid:RESTORE BREATHING; IF REQUIRED. SKIN: REMOVE WITH SOAP AND
WATER. EYES: FLUSH WITH WATER.

===== Fire Fighting Measures =====

Flash Point:55F TCC
Lower Limits:1.0%
Upper Limits:7.0%
Extinguishing Media:USE FO

AM, CO2, STEAM, WATER FOG, DRY CHEMICALS

Fire Fighting Procedures:DON'T USE WATER, EXCLUDE AIR, CONSULT LOCAL FIRE MARSHAL.

Unusual Fire/Explosion Hazard:VAPOR FORMS EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER & LOWER EXPLOSION LIMITS. WEAR SCBA.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID OPEN FLAME OR SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. ABSORB SMALL SPILLSN DRY ABSORPTION MEDIA. USE SPARK-PROOF TOOLS FOR LARGE SPILL

S.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES & SPARK SOURCES. AVOID SPLASH-FILLING. PROVIDE ADEQUATE VENTILATION. AVOID EESSIVE HEAT. FLASH POINT UNDER 70F.

Other Precautions:PROLONGED EXPOSURE TO DUST FROM SANDING, GRINDING OR BLASTING MAY CAUSE LUNG DISORDERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC CANISTER MASK OR AIR PACK.

Ventilation:LOCAL

EXHAUST/MECHANICAL TO KEEP