

PORTER PAINT CO -- 351,GRAY,ZINC-LOCK INORGANIC ZINC,PRIMER -- 8010-00-145-0189

=====
Product Identification
=====

Product ID:351,GRAY,ZINC-LOCK INORGANIC ZINC,PRIMER

MSDS Date:01/01/1987

FSC:8010

NIIN:00-145-0189

MSDS Number: BDCDS

=== Responsible Party ===

Company Name:PORTER PAINT CO

Address:400 S 13TH ST

City:LOUISVILLE

State:KY

ZIP:40203-1714

Country:US

CAGE:50411

=== Contractor Identificati

on ===

Company Name:COURTAULDS COATINGS INC

Address:400 S 13TH STREET

Box:City:LOUISVILLE

State:KY

ZIP:40203-1714

Country:US

Phone:502-588-9651

CAGE:50411

=====
Composition/Information on Ingredients
=====

Ingred Name:SEC-BUTYL ALCOHOL (SARA III)

CAS:78-92-2

RTECS #:EO1750000

Fraction by Wt: 45%

OSHA PEL:150 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:N-PROPYL ALCOHOL

CAS:71-23-8

RTECS #:UH8225000

Fraction by Wt: 5%

OSHA PEL:200 PPM/250 STEL

ACGIH TLV:S,200PPM/250STEL9192

Ingr

ed Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 5%

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 5%

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TRICHLOROETHYLENE (SARA III)

CAS:79-01-6

RTECS #:KX4550000

Fraction by Wt: 5%

OSHA PEL:100 PPM/100 STEL

ACGIH TLV:50 PPM/100,A5

STEL;93

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:INHAL:IRRIT RESP TRACT OR ACUTE NERVOUS SYSTEM
CAUSING HDCH,DIZZ OR NAUS.EYE,SKIN:PRIMARY IRRITATION

=====
===== First Aid Measures =====

First Aid:INHAL:REMOVE FROM EXPOS.KEEP WARM AND QUIET.CALL
MD.EYES:FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST
15 MINUTES.TAKE TO PHYSICIAN FOR MEDICAL TREATM
ENT.SKIN:WASH
AFFECTED AREAS WITH LAR GE AMOUNTS OF WATER.REMOVE CONTAM CLOTHING.

=====
===== Fire Fighting Measures =====

Flash Point:66F,19C SCC

Lower Limits:0.7

Upper Limits:1.0

Extinguishing Media:FOAM,DRY CHEMICAL,CO*2

Fire Fighting Procedures:KEEP CONTNR TIGHT CLOSED.KEEP FROM IGNIT
SOURCE.WEAR SCBA.

Unusual Fire/Explosion Hazard:CLOSED CONTNR MAY EXPLO.AVOID EXPOS TO
DECOMP.IF NO ELECTRICITY,WATER SPRAY W/ FOG NOZ USED TO COOL.

=====

Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT SURFACES & ELECTRICAL,STATIC OR FRICTION SPARKS).AVOID BREATHING VAPORS,WEAR APPROVED(NIOSH OR MSHA) RESPIRATOR AND VENTILATE AREA.REMOVE WITH INERT ABSORBENT SUCH AS SAND,KITTY LITER,ETC & USE NON-SPARK TOOL

===== Handling and Storage =====

Handling and Storage Precautions:SECURE CLOSURES & KEEP CONTAINERS UPRIGHT TO PREVENT LEAKAGE.DO NOT STORE ABOVE 120F.DO NOT TAKE INTERNALLY.WASH HANDS BEFORE EATING OR SMOKING.

Other Precautions:DO NOT GET IN EYES,SKIN-AVOID BREATH VAP OR SPRAY MIST.KEEP AWAY FROM IGNIT SOURCE.GROUND CONTNR WHEN POURING.AVOID FREE FALL OF LIQ ABOVE FEW INCH.USE ONLY NON-FERROUS TOOLS,NON-SPARKING SHOE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD EQUIP,ONLY.IN CONFINED AREA,AIR-LINE RESP,HOOD-SUP

Ventilation

:GEN DILUT OR LOCAL EXHST TO KEEP