

AMERICAN GAS AND CHEMICAL COMPANY,LTD -- FLAW FINDER SD-80D CLEANER (PRE 1/1988) --
6850-00-145-0255

===== Product Identification =====

Product ID:FLAW FINDER SD-80D CLEANER (PRE 1/1988)

MSDS Date:01/01/1987

FSC:6850

NIIN:00-145-0255

Kit Part:Y

MSDS Number: BDCFB

=== Responsible Party ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07

647-1904

Country:US

Info Phone Num:800-526-1008

Emergency Phone Num:201-767-7300

CAGE:03530

=== Contractor Identification ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Phone:201-767-7300

CAGE:03530

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON

Fraction by Wt: 100%

ACGIH TLV:100 PPM

Ingred Name:CARBON DIOXIDE

CAS:124-38-9

RTECS #:FF6400000

Fraction by

Wt: UNK
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:INHALED:HIGH VAPOR CONC. MAY RESULT IN SYMPTOMS
FROM MILD DEPRESS. CONVULSIONS TO UNCONSCIOUSNESS.

=====
First Aid Measures
=====

First Aid:SKIN:WASH WITH SOAP & WATER.EYES:FLUSH WITH
WATER.I
NGESTION:DON'T INDUCE VOMITING.INHALATION:REMOVE TO FRESH
AIR.GIVE CPR/OXYGEN IF NEED.KEEP WARM & QUIET.REMOVE CONTAMINATED
CLOTHING.NEVER GIVE ANYTH ING BY MOUTH TO UNCONSCIOUS PERSON.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:AEROSOL
Lower Limits:0.9
Upper Limits:6.0
Extinguishing Media:CARBON DIOXIDE,FOAM,DRY CHEM & WATER FOG OR SPRAY.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
USE WATER SPRA
Y TO COOL CONTAINER.
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA
WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS
SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING
TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

=====
Handling and Storage
=====

Handling and Storage Prec

autions:STORE IN COOL,DRY,WELL VENT,LOW FIRE
RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT.
KEEP CONTAINERS TIGHTLY CLOSED.
Other Precautions:WARNING:COMBUSTION.AVOID PROLONGED OR REPEATED
CONTACT.REMOVE CONTAMINATED CLOTHING.WASH SKIN WITH SOAP & WATER
AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR HOSE
MASK IF NEEDED.

Ventilation:LOCAL EXHAUST-FACE VE
LOCITY 60FPM.MECH-EXPLOS PROOF EQUIP.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:HYDROCARBON-INSOLUBLE APRON IF NEEDED.

Supplemental Safety and Health

KEY1:J7. THIS PRODUCT IS A KIT CONSISTING OF THREE PARTS.

CLEANER/REMOVER HAS PNI A, PENETRANT HAS PNI B AND DEVELOPER HAS
PNI C, SAME NSN.

===== Physical/Chemical Properties =====

HCC:V3

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:313-347F

Vapor Pres: