GULF OIL CO - US -- GULF SYNFLUID TS-741 -- 9150-00-149-7432 Product ID:GULF SYNFLUID TS-741 MSDS Date:01/01/1985 FSC:9150 NIIN:00-149-7432 MSDS Number: BDCPP === Responsible Party === Company Name: GULF OIL CO - US Emergency Phone Num:713-226-1011 CAGE:KO307 === Contractor Identification === Company Name: GULF OIL CO - US CAGE:KO307 Company Name: GULF OIL CO U.S. A DIV OF GULF OIL CORP Box:1519 City:HOUSTON State:TX ZIP:77001 Country:US CAGE:34252 ======= Composition/Information on Ingredients ======== Ingred Name: NO INGREDIENT FOR THIS FORMULATION INGREDIENT ============= Hazards Identification ======================== Effects of Overexposure: SKIN: REPEATED CONTACT MAY CAUSE IRRITATION. MIST & FUMES MAY IRRIT MUCOUS MEMBRANES. First Aid:SKIN: REMOVE BY WIP ING THEN SOAP & WATER WASH, EYES: FLUSH W/COPIOUS AMT OF WATER. INHAL: REMOVE FROM EXPOSURE TO FUMES, MISTS. INTERN: GIVE 2-4 OZ VEG OR OLIVE OIL & 1-2 OZ ACTIVATED CHARCOAL. SEE MD. Flash Point:420F CC Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, FOG Fire Fighting Procedures: CAREFUL USE OF FOAM & WATER TO PREVENT **EXCESSIVE FROTHING** Unusual Fire/Explosion Hazard: SLIGHT WHEN EXPOSED TO HEAT OR FLAME

View NSN Online: https://aerobasegroup.com/nsn/9150-00-149-7432

, CAN REACT W/OXIDIZING MATERIALS. COMBUSTIBLE.
======== Accidental Release Measures ==========
Spill Release Procedures:STOP FLOW. REMOVE ALL SOURCES OF IGNITION. AVOID SKIN CONTACT & INHALING VAPOR OR MIST. ABSORB OR SCRAPE UP.
=========== Handling and Storage ============
Handling and Storage Precautions:AVOID FREQUENT OR PROLONGED SKIN CONTACT, INHAL OF FUMES, MIST, VAPORS. HANDLE & STORE W/METHODS APPROVED FOR COMBUSTIBLE HYDROCA RBONS.
Other Precautions:DO NOT WEAR OIL-SOAKED CLOTHING
====== Exposure Controls/Personal Protection ========
Respiratory Protection:FOR VAPORS & MIST EXCEEDING TLV THERMAL PROCESSING, SPRAY APPLICATION Protective Gloves:BUTYL RUBBER
Other Protective Equipment:OIL IMPERVIOUS OR PROTECTIVE GARMENT AS REQUIRED
Supplemental Safety and Health BP IS 190 - 195C, VAPOR PRESSURE IS NEGLIGIBLE.
========= Physical/Chemical Properties ==========
HCC:V6 Boiling P t:B.P. Text:374 - 384F Spec Gravity:0.8438 Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR, PALE, LUBRICATIANG OIL
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:HEAT MAY LIBERATE SMALL QUANTITIES OF FREE PHENOL
======= Disposal Considerations ==========
Waste Disposal Methods:INCINERATE IN ACCORDANCE W/LOCAL, STATE, FED REGULATIONS.
Disclaimer (provide

d with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.