

CLAYTON CHEMICAL CO. -- DA2105,CLAYTON AERIAL DEVELOPER/REPL,PART C --  
6750-00-151-6035

=====  
Product Identification  
=====

Product ID:DA2105,CLAYTON AERIAL DEVELOPER/REPL,PART C

MSDS Date:02/14/1991

FSC:6750

NIIN:00-151-6035

Kit Part:Y

MSDS Number: BDCRD

=== Responsible Party ===

Company Name:CLAYTON CHEMICAL CO.

Address:13310 S. FIGUEROA ST

City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Info Pho

ne Num:213-538-9530

Emergency Phone Num:213-538-9530

CAGE:61803

=== Contractor Identification ===

Company Name:CLAYTON CHEMICAL CO.

Address:13310 S. FIGUEROA STREET

Box:City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Phone:310-538-9530/800-424-9300(CHEMTREC)

CAGE:61803

Company Name:CLAYTON CHEMICAL CO., A DIV OF VARICHEM CORP

Address:RR 1

Box:276-Z

City:HEATHSVILLE

State:VA

ZIP:22473

Country:US

Phone:703-759-9399

CAGE:6W820

=====  
Composition/Information on Ingredients  
=====

In

Product Name:HYDROQUINONE (SARA III)

CAS:123-31-9

RTECS #:MX3500000

Fraction by Wt: 41C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, OR ALCOHOL FOG.

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. SMALL SPILL: ABSORB WITH INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLU

SH AREA WITH WATER. LARGE SPILL: DIKE AHEAD TO PREVENT FURTHER MOVEMENT. ABSORB WITH ABSORBENT.NEUTRALIZE LIQUID WITH WEAK ALKALI (NAHCO3)

Neutralizing Agent:SODIUM BICARBONATE DILUTE SOLUTION.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY FROM ACIDS OR OXIDIZERS.

Other Precautions:THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT SHOULD BE MADE BY THE MATERIAL USER BASED ON THE PARTICULAR CONDITIONS

WHERE THE MATERIAL IS TO BE USED TOGETHER WITH INFORMATION CONTAINED IN THIS MSDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED

Ventilation:LOCAL EXHAUST REQUIRED. MECHANICAL (GENERAL) OPTIONAL.

Protective Gloves:RUBBER/NEOPRENE

Eye Protection:CHEMICAL SAFETY GOGGLES

Other Protective Equipment:RUBBER APRON AND BOOTS IF SPILLS ARE LIKELY.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.REMOVE & LAUNDER

CONTAMINATED CLOTHING.

Supplemental Safety and Health

KEY1:F5. THIS IS PART C OF A 3-PART PRODUCTS. FOR OTHER PARTS,SEE PNI A & B,SAME NSN. PER MANUFACTURER,CAT # DA2105. PREVIOUSLY CAT NO WAS XR-DA2105.

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:B.P. Text:>212F,>100C

Spec Gravity:1.119

pH:>4.0

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT STRAW COLORED LIQUID. ODOR OF AMINE (FISHY ODOR) ODOR.

===== Stability and

Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
STRONG MINERAL ACIDS, STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid: HIGH TEMPERATURES  
Hazardous Decomposition Products: SULFUR DIOXIDE GAS

===== Disposal Considerations =====

Waste Disposal Methods: NEUTRALIZE WITH SODIUM BICARBONATE AND DISPOSE THROUGH WASTE TREATMENT PLANT IN COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.