

3M COMPANY -- SCOTCHGRIP INDUSTRIAL ADHESIVE 2126, TY III -- 8040-00-152-0067

=====
Product Identification
=====

Product ID:SCOTCHGRIP INDUSTRIAL ADHESIVE 2126, TY III

MSDS Date:01/01/1985

FSC:8040

NIIN:00-152-0067

MSDS Number: BDCVH

=== Responsible Party ===

Company Name:3M COMPANY

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:

612-733-1110

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:LIQ IRRIT TO EYES. MAY DEFAT SKIN. VAPORS MAY BE IRRIT TO NOSE, THROAT, EYES. POSS SLIGHT NARCOSIS.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH W/ PLENTY OF WATER. CALL A PHYSICIAN. SKIN: WASH W/ SOAP & WATER. INH: PROVIDE FRESH AIR.

=====
Fire Fighting Measures
=====

Flash Point:30F CC

Lower Limits:1.8

Upper Limits:10.

Extinguishing Media:CO*2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:EXTINGUISH ALL IGNITION SOURCES. COLLECT SPILLED MATERIAL W/ NON-SPARKING TOOLS & PLACE IN A CLOSED METAL CONTAINER.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & FLAMES. USE W/ ADEQ VENT. AVOID PROLONGED OR REPEATED SKIN CONTACT. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:AVOID EYE CONTACT. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS.

=====
Exposure Controls/Personal Protection
=====

Ventilation:MFR RECM LOCAL EXHAUST

Protective Gloves:RUBBER

,NEOPRENE

Eye Protection:CHEMICAL GOGGLES

Supplemental Safety and Health

VAPOR DENSITY IS BASED ON MEK. % VOLATILE BY WT: 70-80.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:176F (MEK)

Vapor Density:2.48

Spec Gravity:0.9

Evaporation Rate & Reference:2.7 (ETHER)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:KETONE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

=====

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM INCINERATE PROPERLY. DISPOSE IAW FED.,
STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.