View NSN Online: https://aerobasegroup.com/nsn/8010-00-160-5788

Product ID:TT-T-266D THINNER MSDS Date:01/01/1985 FSC:8010 NIIN:00-160-5788 MSDS Number: BDDGD === Responsible Party === Company Name:STIC-ADHESIVES PRODUCTS CO., INC. Emergency Phone Num:(213)268-2956 CAGE:KO353 === Contractor Identification === Company Name:STIC-ADHESIVE PRODUCTS CO INC

Address:3950 MEDFORD ST Box:City:LOS ANGELES State:CA ZIP:90063-1675 Country:US CAGE:1BH90 Company Name:STIC-ADHESIVES PRODUCTS CO., INC. CAGE:KO353

Ingred Name:N-BUTYL ALCOHOL (SARA III) CAS:71-36-3 RTECS #:EO1400000 OSHA PEL:100 PPM ACGIH TLV:S, C 50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 OSHA PEL:200 PPM/300 STEL AC

GIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III) CAS:123-86-4 RTECS #:AF7350000 OSHA PEL:150 PPM/200 STEL ACGIH TLV:150 PPM/200STEL;9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III) CAS:78-83-1 RTECS #:NP9625000 OSHA PEL:100 PPM ACGIH TLV:50 P PM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Effects of Overexposure:DRYING OF SKIN;EYE IRRIT;EXCESSIVE INHALATION MAY CAUSE ANESTH, HDCH, DIZ, NAUSEA, UPPER RESP IRRT

First Aid:INH:REMOVE TO FRESH AIR, APPLY ARTIF RESP IF NECESSARY. CALL A PHYSICIAN. SKIN: WASH W/MILD SOAP & WATER, APPLY MILD SKIN CREAM;IF SEVERE, CONTACT PHYSICIAN. EYE: FLUSH W/WATER, CALL PHYSICIAN. INGEST: CALL A PHYSICIAN.

Flash Point:27F TCC

Extinguishing Media:FOAM, CO*2, DRY CHEMICALS. DO NOT USE WATER. Fire Fighting Procedures:WEAR SELF-CONT BRTH APPAR. USE WATER AS COOLING/DILTN MEDIUM

Unusual Fire/Explosion Hazard: AVOID SPARKS, FIRE OR HOT METAL SURFACES

Spill Release Procedures: AVOID SPARKS, FIRE & HOT MET

AL SURFACES. FLUSH W/WATER INTO A NON-HAZARDOUS RETAINING AREA OR CONTAINER. SMALL QUANTITIES MAY BE ABSORBED INTO AN APPROPRIATE ABSORBANT.

 Handling and Storage Precautions: KEEP COOL & AWAY FROM SOURCES OF IGNITION. USE W/ADEQUATE VENTILATION.
 Other Precautions: AVOID PERSONAL CONTACT. WASH OFF SPILLED LIQUID. REMOVE WET CLOTHES.

Respiratory

Protection:NIOSH/MSGHA APPRVD RESPIRATORY PROTECTION FOR PARTICULAR CONDITIONS.
Ventilation:SUFFICIENT TO KEEP WORKROOM CONC BELOW TLV
Protective Gloves:IMPERMEABLE
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:IMPERVIOUS GLOVES OR BARRIER CREAMS.
Supplemental Safety and Health
ADD INGRED:ISOBUTYL ACETATE, TLV OF 150 PPM; ISOPROPYL ALCOHOL, TLV OF 400 PPM; NAPHTHA,ALIPHATIC. VAP PRESSURE IS MEASURED AT 20C. INGRED INFORMATION IS BASED ON THE SPECIFICATION.

HCC:F3 Boiling Pt:B.P. Text:192-239F Vapor Pres:56 Vapor Density:3.3 Spec Gravity:0.822 Evaporation Rate & amp; Reference:2.4(N-BU AC) Solubility in Water:MODERATE Appearance and Odor:CLEAR,COLORLESS; CHARACTERISTIC ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS,STRONG ACIDS OR BASES, SELECT AMINES Stability Conditi

on to Avoid:HEAT,SPARKS, OPEN FLAME,FIRE Hazardous Decomposition Products:THERMAL DECOMP IN PRESENCE O AIR MAY YIELD CO &/OR CO*2

Waste Disposal Methods: DISPOSE IAW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, w arrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.