

CSD, INC -- A-A-857B -- 8010-00-160-5788

=====
===== Product Identification =====

Product ID:A-A-857B
MSDS Date:01/01/1987
FSC:8010
NIIN:00-160-5788
MSDS Number: BDDGF
=== Responsible Party ===
Company Name:CSD, INC
Address:5 HACKBURY ST
Box:687
City:CONROE
State:TX
ZIP:77305
Country:US
Info Phone Num:409-756-1065/713-797-0395(MEDICAL)
Emergency Phone Num:713-923-6641/800-424-9300(CHEMTREC)
CAGE:0LWP6
=== Contractor Identification ===
Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC
Address:2210 HACKBERRY LN
Box:687
City:CONROE
State:TX
ZIP:77305
Country:US
Phone:409-756-1065
CAGE:4N760
Company Name:CSD, INC
Box:687
City:CONROE
State:TX
ZIP:77305
Country:US
Phone:800-424-9300
CAGE:0LWP6

=====
===== Composition/Information on Ingredients =====

Ingred Name:SOLVENTS
Fraction by Wt: 100%

=====
===== Hazards Identification =====

Effects of Overexpos

ure:INHAL:ANEST.IRRITATES RESPIRAT TRACT.MAY CAUS
NERV SYS DEPRESSION BY HDACH,DIZZ,STAGG,CONFUSION,COMA

=====
First Aid Measures
=====

First Aid:EYES & SKIN:FLUSH W/WATER F/AT LEAST 15 MIN.IF IRRITATED GET
MEDICAL ATTN.VAPORS:REMOV FR EXPOSURE.RESTORE BREATHING.
SWALLOWING:CALL A DR IMMEDIATE.DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point:38F TCC 3C TCC
Lower Limits:1.0
Extinguishing Media:
CO*2, DRY CHEMICAL,OR FOAM
Fire Fighting Procedures:WATR SPRAY MAY BE INEFFECT,BT CN PROTCT
FIREFIGHT/COOL CONTN
Unusual Fire/Explosion Hazard:KEEP CONTNR TIGHTLY CLOSED.KEEP AWAY FROM
HEAT,SPARKS,ELECTR EQPMT & OPEN FLAME.CLOS CONTR MAY EXPL

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOV ALL SOURCES OF IGNITION. AVOID BREATHING
VAPOR.VENTILATE. REMOV W/INERT ABSORBENT, NON-SPARKING PRODUCTS.

=====
Handling and S
torage
=====

Handling and Storage Precautions:VAPS MAY IGNITE EXPLOSIV.VAPRS MAY
SPREAD LONG DISTANCES.PREVNT BLDUP OF VAPS.EXTING ALL PILOT LGTS &
TURN OFF HEATRS,NON-EXPLOSION PROOF ELECT EQPMT.
Other Precautions:DO NOT STORE ABOVE 120F.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:VENTIL TO KEEP AIR BELOW 65 PPM.IF OVER TLV,USE
SELF-CONTND AIR PACK.
Ventilation:LOC EXHAUST-PREFERABLE,MECH-ACCEPTABLE
Protective Gloves
:PREFERABLE
Eye Protection:CHEM GOGGLES
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:B.P. Text:268
Vapor Pres:48
Vapor Density:3.0
Spec Gravity:.822
Evaporation Rate & Reference:ETHER 4.9
Solubility in Water:APPRECIABLE
Appearance and Odor:CLEAR, WATER-WHITE, KETONE ODOR
Percent Volatiles by Volume:100%

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STR

ONG OXIDIZERS

Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE FROM BURNING.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ACCORDING TO AIR POLLUTION REGULATIONS.DO NOT INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of Am

erica in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.