

CORONADO PAINT CO -- VARNISH, SPAR, TT-V-121 -- 8010-00-160-5852

=====
Product Identification
=====

Product ID:VARNISH, SPAR, TT-V-121

MSDS Date:01/01/1985

FSC:8010

NIIN:00-160-5852

MSDS Number: BDDHW

=== Responsible Party ===

Company Name:CORONADO PAINT CO

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

Info Phone Num:904-428-6461 / FAX 904-427-7130

Emergency

Phone Num:904-428-6461

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:AROMATIC & ALIPHATIC HYDROCARBON

RTECS #:ZE2190000

Fraction by Wt: 44.7%

ACGIH TLV:200 PPM

Ingred Name:POLYURETHANE & ALKYD RESIN

Fraction by Wt: 55.3%

ACGIH TLV:NO HAZARD

=====

Hazards Identification =====

Effects of Overexposure:PRODUCES SEVERE EYE IRRITATION, DRYING OF SKIN.
EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS.

===== First Aid Measures =====

First Aid:EYE CONTACT-FLUSH WITH WATER. SKIN CONTACT-WASH WITH MILD
SOAP AND WATER AND APPLY SKIN CREAM. INHALATION-REMOVE TO FRESH AIR
AND CALL A PHYSICIAN, APPLY ARTIFICIAL RESPIRATION IF NECESSARY.

===== Fire Fighting Measures
=====

Flash Point:92F SETA

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:TREAT AS CLASS B FIRE.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH
AIR.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO
RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE, OR HOT
METAL SURFACES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN
FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED
CONTACT WITH SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED NIOSH APPROVED PROTECTION IF TLV
IS EXCEEDED.

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:YES

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

S

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:280
Vapor Pres:6
Vapor Density:3.7
Spec Gravity:0.92
Evaporation Rate & Reference:0.6
Solubility in Water:VERY SLIGHT
Appearance and Odor:CLEAR LIQUID, PETROLEUM DISTILLATE ODOR.
Percent Volatiles by Volume:52.9

===== Stability and Reactivity Data =====

Stabil
ity Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HEAT, SPARKS OPEN FLAMES OR FIRES.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON
MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:LAND FILL, INCINERATION UNDER SAFE AND
SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of t
he Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.