

ENTERPRISE CHEMICAL COATING CO DIV OF INSILCO CORP -- OLEORESINOUS VARNISH --
8010-00-160-5852

===== Product Identification =====

Product ID:OLEORESINOUS VARNISH

MSDS Date:01/01/1985

FSC:8010

NIIN:00-160-5852

MSDS Number: BDDHX

=== Responsible Party ===

Company Name:ENTERPRISE CHEMICAL COATING CO DIV OF INSILCO CORP

Address:2841 S ASHLAND

City:CHICAGO

State:IL

ZIP:60608-5322

Country:US

Emergency

Phone Num:312-376-9150

CAGE:60035

=== Contractor Identification ===

Company Name:ENTERPRISE CHEMICAL COATING CO DIV OF INSILCO CORP

Address:2841 S ASHLAND

Box:City:CHICAGO

State:IL

ZIP:60608-5322

Country:US

CAGE:60035

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 39.5%

OSHA PEL:100 PPM

Ingred Name:CELLOSOLVE ACETATE

RTECS #:KK8550000

Fraction by Wt: 5.6%

ACGIH TLV:500 PPM

=====
Hazards Identification
=====

Effects of Overexposure:EXCESSIVE,PROLONGED INHALATION MAY RESULT IN HEADACHE,NAUSEA,AND MILD EYE IRRITATION

=====
First Aid Measures
=====

First Aid:EYE:FLUSH WITH WATER.CALL DR. SKIN:WIPE RESIN OFF AND WASH AFFECTED AREA. INGEST:DO NOT INDUCE VOMIT. CALL DR.

=====
Fire Fighting Measures
=====

Flash Point:40/104 SCC

Lower Limits:1.1

Extinguish

ing Media:FOAM,CO*2,DRY CHEM.,SAND.

Fire Fighting Procedures:CONTAINERS MAY RUPTURE DUE TO EXCESSIVE HEAT AND PRESSURE

Unusual Fire/Explosion Hazard:AVOID USE OF WATER.

=====
Accidental Release Measures
=====

Spill Release Procedures:WITH OR WITHOUT SOLID ABSORBENT,SHOVEL OR SCOOP INTO CONTAINER.SOLVENT RINSE AND WASH DOWN AREA KEEP WELL VENTILATED.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID FLAME,HIGH TEMP.STORAGE AND LOCALIZED SOLVENT VAPOR BUILD-UP.

Other Precautions:GROUND EQUIP.TO AVOID ELECTRICAL SPARKING.DO NOT TAKE INTERNALLY AND AVOID PROLONGED CONTACT OR INHALATION.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT NORMALLY NECESSARY

Ventilation:LOCAL:TO REDUCE VAPORS AND REDUCE FIRE HAZARD.

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GOGGLES OR GLASSES

Other Protective Equipment:EQUIP.COMPLUING WITH OSHA 1910.

135.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300-400 F

Vapor Pres:2

Vapor Density:>1

Spec Gravity:0.90

Evaporation Rate & Reference:TOLUEN=1: