View NSN Online: https://aerobasegroup.com/nsn/8010-00-160-6911

CARROLL/LTD INC -- CARROL 4-1/2 CUT WHITE SHELLAC -- 8010-00-160-6911

Product ID:CARROL 4-1/2 CUT WHITE SHELLAC MSDS Date:01/01/1985 FSC:8010 NIIN:00-160-6911 **MSDS Number: BDDJG** === Responsible Party === Company Name: CARROLL/LTD INC Address:2656 SALMON ST City:PHILADELPHIA State:PA ZIP:19125-4034 Country:US CAGE:59973 === Contractor Identification === Company Na me:CARROLL/LTD INC Address:2656 SALMON ST Box:City:PHILADELPHIA State:PA ZIP:19125-4034 Country:US CAGE:59973 Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT Effects of Overexposure: EYE, SKIN, THROAT, IRRITANT. HEADACHE, DROWSINESS, INTOXIATION

First Aid:REMOVE TO FRESH AI

| R, GIVE ARTIFICIAL RESPIRATION IF NECESSARY. WASH SKIN WELL. FLUSH EYES 15 MINUTES WITH WATER. CALL MD. GIVE OXYGEN IF NECESSARY |
|---|
| ====================================== |
| Flash Point:50F,L0C TCC Lower Limits:4.3 Upper Limits:19.0 Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL Fire Fighting Procedures:WATER WILL SCATTER AND SPREAD FIRE. NO NOT USE Unusual Fire/Explosion Hazard:KEEP FROM HEAT, SPARKS, FIRE, FLAME. USE EXPLOSION-PROOF ELECTRICAL EQUIPMEN T. VENTILATE AREA |
| ====================================== |
| Spill Release Procedures:REMOVE ALL SOURCES OF HEAT, SPARKS. DO NOT BREATHE FUMES. AOVID BODILY CONTACT. CONTAIN SPILL IN DIKED AREA TO MINIMIZE VAPORS |
| ====================================== |
| Handling and Storage Precautions:STORE BELOW 100F DEGREES. USE GLASS, PLASTIC LINED STEEL OR TIN CONTAINERS TO TRANSFER MATERIAL Other Precautions:NFPA BULLETINS 30 AND 77 |
| ===== ======= Exposure Controls/Personal Protection ==================================== |
| Respiratory Protection:ALL PURPOSE CANISTER Ventilation:LOCAL, MECHANICAL, FLOOR AND LOW AREAS Protective Gloves:RUBBER Eye Protection:SAFETY GOGGLES Supplemental Safety and Health SOLVENT IS DENATURED ALCOHOL, TR590, DENATURED ALCOHOL |
| ====================================== |
| HCC:F2 Boiling Pt:B.P. Text:176F,80C Vapor Pres:44 Vapor Density:1.6 Spec Gravity:0.9 Evaporation Rate & amp; Reference:1.7 N-BUTY |

L ACETAT Solubility in Water:MODERATE Appearance and Odor:VISCOUS LIQUID. NONRESIDUAL ODOR. COLOR-MILKY WHIT

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIAL Hazardous Decomposition Products:CARBON MONOXIDE

Waste Disposal Methods: MAY BE BURNED IN COMBUSTION CHAMBER BY ENGINEER

Disclaimer (provided with this information by the compiling agencie s):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.