

MAGNAFLUX CORPORATION -- SKC-W SPOTCHECK REMOVER/EMULSIFIER -- 6850-00-160-8481

=====
Product Identification
=====

Product ID:SKC-W SPOTCHECK REMOVER/EMULSIFIER

MSDS Date:07/17/1986

FSC:6850

NIIN:00-160-8481

MSDS Number: BDDJN

=== Responsible Party ===

Company Name:MAGNAFLUX CORPORATION

Address:7300 W. LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:312-867-8000

Eme

Agency Phone Num:312-867-8000

Preparer's Name:BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

=====
Composition/Information on Ingredients
=====

Ingred Name:HIGH FLASH PETROLEUM NAPHTHA

CAS:64742-89-8

Fraction by Wt: 90.0%

OSHA PEL:500PPM

ACGIH TLV:500PPM

Ingred Name:CARBON DIOXIDE

CAS:124-38-9

RTECS #:FF

6400000

Fraction by Wt: 03.0%

OSHA PEL:5000 PPM

ACGIH TLV:5000PPM/30000STEL;93

Ingred Name:UNIDENTIFIED COMPONENTS;PER MFR,CONTAINS NO OTHER
INGREDIENTS SUSPECTED OF BEING HAZARDOUS I/A/W INFO IN
29CFR1910.1200.

Fraction by Wt: 07.0%

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRITATES EYES.

Explanation of Carcinogenicity:PER MFR,CONTAINS NO KNOWN OR SUSPECTED
CARC

INOGENS LISTED WITH OSHA/IARC/NTP.

Effects of Overexposure:INHALATION:SPRAY MIST MAY IRRITATE BREATHING
PASSAGES; EYES:LIQUID CONTACT MAY CAUSE IRRITATION; SKIN:SOLVENT IN
THE PRODUCT MAY IRRITATE SKIN; INGESTION:NOT NOTED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. IF BREATHING IS
DIFFICULT,GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES
.WASH OFF

WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET
MEDICAL ATTN; EYES:IM MEDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF
RUNNING WATER,AND GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:CARBON DIOXIDE,FOAM.

Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT
SPRAY WATER ON BURNING SKC-W.

Unusual Fire/Explosion Hazard:AEROSOL CANS CAN BURST IF HEATED ABOVE
130F(54.4C).

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP
UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG
QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB
LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE
TANKS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES I

N WELL

VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.DO NOT SPRAY INTO FLAME,ARCS,OR RED HOT SURFACES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR RESPIRATOR WITH CHEMICAL CARTRIDGE.IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ven

tilation:GENERAL VENTILATION TO KEEP BELOW 350PPM OF TLV LIMIT.

Protective Gloves:NITRILE RUBBER GLOVES.

Eye Protection:FULL GOGGLES.

Other Protective Equipment:USE IN SPRAY BOOTH OR NEXT TO AN EXHAUST VENT TO CARRY VAPORS AWAY FROM OCCUPIED AREAS.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING MATERIAL.LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

NSN FOR CLASS (2) OF MIL-I-25135,REV D,& QPL-25135-15;THIS ENTRY DESCRIBES SKC-W CLEANER/REMOVER.

==

=====
===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text:N/R(AEROSOL

Spec Gravity:0.8 OF BULK LIQ

Evaporation Rate & Reference:0.7 (ETHER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:THIN,CLEAR,COLORLESS LIQUID BEFORE FILLING IN AEROSOL CANS.

Percent Volatiles by Volume:90.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALI METALS.

Stability Condition to Avoid:HEAT/HIGH T

TEMPERATURES.

Hazardous Decomposition Products:PHOSGENE,HYDROCHLORIC ACID GAS,&
OXIDES OF CARBON.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE
D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL,STATE,LOCAL REGULATIONS; IF LOCAL AUTHORITIES PROHIBIT
DUMPING RINSINGS DOWN THE SEWER, PURIFY RINSINGS WIT MAGNAFLUX
WASTEWATERSYSTEM.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.