

MARSH COMPANY -- K-TYPE STENCIL INK,BLACK -- 7510-00-161-0811

=====  
Product Identification  
=====

Product ID:K-TYPE STENCIL INK,BLACK

MSDS Date:12/02/1992

FSC:7510

NIIN:00-161-0811

MSDS Number: BDDJQ

=== Responsible Party ===

Company Name:MARSH COMPANY

Address:707 EAST B STREET

Box:388

City:BELLEVILLE

State:IL

ZIP:62220

Country:US

Info Phone Num:618-234-1122

Emergency Phone Num:618-234-1122

CAGE:F

O646

=== Contractor Identification ===

Company Name:MARSH COMPANY

Address:707 E. B STREET

City:BELLEVILLE

State:IL

ZIP:62220

Phone:(618) 234-1122

CAGE:FO646

Company Name:MARSH STENCIL MACHINE CO

Address:707-EAST B STREET

Box:388

City:BELLEVILLE

State:IL

ZIP:62222

Country:US

Phone:618-234-1122

CAGE:38512

=====  
Composition/Information on Ingredients  
=====

Ingred Name:STODDARD SOLVENT; (MINERAL SPIRITS)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 5-10%

OSHA PEL:500 PPM

ACGIH

TLV:100 PPM; 9293

Ingred Name:KEROSENE; (FUEL OIL #1)  
CAS:8008-20-6  
RTECS #:OA5500000  
Fraction by Wt: 60-100%  
Other REC Limits:5MG/M3 OIL MIST(MFR)

Ingred Name:NAPHTHALENE (SARA III)  
CAS:91-20-3  
RTECS #:QJ0525000  
Fraction by Wt: 1-5%  
OSHA PEL:10 PPM;15 PPM STEL  
ACGIH TLV:10 PPM;15 PPM STEL  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

=====  
===== Hazards Identification =====  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES I  
ngestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:MODERATELY TOXIC BY INGESTION &  
OTHER ROUTES. IRRITANT TO SKIN, MUCOUS MEMBRANE & SEVERE EYE  
IRRITANT. NARCOTIC IN HIGH CONCENTRATIONS. CHRONIC:OVEREXPOSURE CAN  
CAUSE KIDNEY DAMAGE.  
Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures  
=====

First Aid:INGEST:DO NOT INDUCE VOMITING. CALL MD IMMEDIATELY.  
SKIN:REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY W/SOAP & WATER.  
CALL MD IF NECESSARY. EYE:FLUSH IMMEDIATELY W/WATER FOR AT LEAST 15  
MINUTES. CALL MD IMMEDIATELY. INHAL:REMOVE TO FRESH AIR. IF  
DISCOMFORT PERSISTS, GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:TCC  
Flash Point:110F,43C  
Extinguishing Media:CARBON DIOXIDE, DRY C

HEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:ISOLATE SPILL FROM SOURCES OF IGNITION.  
CONTAIN SPILL USING SUITABLE ABSORBENT - CONTAINERIZE IN APPROVED DOT CONTAINER FOR PROPER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====  
=====

Handling and Storage Precautions:MATERIAL IS CLASSIFIED AS COMBUSTIBLE  
- KEEP AWAY FROM HEAT & OPEN FLAME.

Other Precautions:HAZARDOUS PRODUCT RESIDUE MAY REMAIN AFTER PRODUCT HAS BEEN REMOVED FROM ITS CONTAINER. DO NOT REUSE "EMPTY" CONTAINER W/OUT COMMERCIAL CLEANING OR RECONDITIONING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR WHERE AIRBORNE LEVELS MAY EXCEED PEL.

Ventilation:LOC

AL EXHAUST & MECHANICAL VENTILATION.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:AS NECESSARY TO AVOID PROLONGED CONTACT.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

SPEC GRAV:0.88-1.4 (H\*2O=1).

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>248F,>120C

Vapor Pres:1

Spec Gravity:SUPP DATA

Evaporation Rate & Reference: