

PRATT & LAMBERT - WICHITA DIVISION -- 725-402 -- 8010-00-161-7425

=====  
Product Identification  
=====

Product ID:725-402

MSDS Date:01/01/1985

FSC:8010

NIIN:00-161-7425

MSDS Number: BDDPD

=== Responsible Party ===

Company Name:PRATT & LAMBERT - WICHITA DIVISION

Emergency Phone Num:316-733-1361

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 35.0%

OSHA PEL:100 PPM

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 0.11%

OSHA PEL:0.05 MG/M3;1910.1

025  
ACGIH TLV:0.15 MG/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:ZINC CHROMATE  
Fraction by Wt: < 5%

Ingred Name:TRIETHYLAMINE (SARA III)  
CAS:121-44-8  
RTECS #:YE0175000  
Fraction by Wt: 0.4%  
OSHA PEL:25 PPM/15 STEL  
ACGIH TLV:10 PPM/15 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

Effects of Overexposure:INHALED-ANESTHETIC, IRRITATE AIRWAY; SKIN/EYE  
IRRITATION HEADACHE, DIZZINESS, COMA,CONFUSION

=====  
===== First Aid Measures =====

First Aid:INCASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER  
WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH  
AIR. CALL A PHYSICIAN IF SYMPTONS PERSIST. PERFORM ARTIFICIAL  
RESPIRATION IF BREATHING HAS STOPPED.

=====  
===== Fire Fighting Measures =====

Flash Point:104 F, 40 C TCC  
Lower Limits:1.1  
Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL; POLYMER  
F  
OAM-LARGE FIRE  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE  
FOR FIREMEN  
Unusual Fire/Explosion Hazard:PRESSURE BUILD-UP FROM EXTREME HEAT MAY  
CAUSE EXPLOSION. USE WATER TO COOL CANS. FOR FIRE:FOGNOZZLES

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT  
SURFACES, & ELECTRICAL, OR FRICTIONAL SPARKS). AVOID BREATHING  
VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AN



APPROVED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the  
suitability of this information to their  
particular situation.