

CORONADO PAINT CO -- THINNER -- 8010-00-162-5289

=====
Product Identification
=====

Product ID:THINNER
MSDS Date:01/01/1987
FSC:8010
NIIN:00-162-5289
MSDS Number: BDDPY
=== Responsible Party ===
Company Name:CORONADO PAINT CO
Address:308 OLD COUNTY RD
Box:308
City:EDGEWATER
State:FL
ZIP:32032-1812
Country:US
Info Phone Num:904-428-6461 / FAX 904-427-7130
Emergency Phone Num:904-428-6461
CAGE:3320

0
=== Contractor Identification ===
Company Name:CORONADO PAINT COMPANY, INC.
Address:308 OLD COUNTY ROAD
Box:City:EDGEWATER
State:FL
ZIP:32132-1812
Country:US
Phone:904-428-6461
CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 40.0%
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71

-36-3
RTECS #:EO1400000
Fraction by Wt: 25.0%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-AMYL ACETATE (SARA III)
CAS:628-63-7
RTECS #:AJ1925000
Fraction by Wt: 10.0%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AROMATIC NAPHTHA
Fraction by Wt: 25.0%

=====
Hazards Identification
=====

Effects of Overexposure:IRRITATION OF EYES,NOSE AND THROAT.
HEAD
ACHE,INTOXICATION & DROWSINESS MAY OCCUR.DRYING OF SKIN

=====
First Aid Measures
=====

First Aid:IN CASE OF CONTACT,FLUSH THOROUGHLY WITH WATER. FOR
INHALATION,REMOVE TO FRESH AIR AND ADMINISTER OXYGEN. CALL
PHYSICIAN.SKIN CONTACT:WASH WITH MILD SOAP & WATER,APPLY A MILD
SKIN CREAM,IN SEVERE CASE S,CONTACT A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:115F SETA
Lower Limits:2.6
Upper Limits:12.6

Extinguishing Media:CO2 OR DRY CHEMICAL EXTINGUISHER OR FOAM
Fire Fighting Procedures:DO NOT USE WATER
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCE OF IGNITION. AVOID BREATHING
OF VAORS OR CONTACT WITH EYES. CONTAIN SPILL IN A DIKED AREA TO
MINIMIZE VAPORS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. IF

NECESSARY

TO TRANSFER CONTENTS TO ANOTHER CONTAINER, GLASS, PLASTIC, SPECIAL LINED STEEL OR TIN ARE ACCEPTABLE

Other Precautions: OTHER HANDLING IN ACCORDANCE WITH NFPA BULLETIN 30 AND 77. AVOID PROLONGED OR REPEATED PERSONAL CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WHERE HIGH CONCENTRATIONS OF VAPOR EXIST, USE ALL PURPOSE CANISTER

Ventilation: LOCAL EXHAUST-FROM FLOOR AND LOW AREAS

Protective Gloves: IMPERMEABLE

Eye Protection

: CHEMICAL GOGGLES

Other Protective Equipment: APRON, BARRIER CREME.

Supplemental Safety and Health

ALL ELECTRICAL EQUIPMENT MUST BE EXPLOSION-PROOF

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 260F

Vapor Pres: 60

Vapor Density: 4.0

Spec Gravity: 0.855

Evaporation Rate & Reference: FASTER THAN NBUACT

Solubility in Water: 11 PERCENT

Appearance and Odor: CLEAR, COLORLESS LIQUID. PUNGENT, FRUITY ODOR.

Percent Volatiles by Volume: 100

=====

= Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZING MATERIALS

Stability Condition to Avoid: EXCESSIVE HEAT, SPARKS, OPEN FLAMES

Hazardous Decomposition Products: CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: IF CUSTOM DISPOSAL SERVICE IS NOT AVAILABLE, LARGE QUANTITIES MAY BE BURNED IN A COMBUSTION CHAMBER BY A COMPETENT ENGINEER

Disclaimer (provided with this information by

the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.