

STERLING LACQUER MFG CO -- THINNER,CELLULOSE-NOTRATE DOPE -- 8010-00-162-5289  
===== Product Identification =====

Product ID:THINNER,CELLULOSE-NOTRATE DOPE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-162-5289

MSDS Number: BDDPZ

=== Responsible Party ===

Company Name:STERLING LACQUER MFG CO

Emergency Phone Num:314-776-4450

CAGE:60003

=== Contractor Identification ===

Company Name:STERLING LACQUER MFG CO

Address:3150 BRANNON AVE

Box:City:ST. LOUIS

State:MO

ZIP:63139-1422

Country:US

Phone:314-776-4450

CAGE:60003

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 7.40%

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ALCOHOL

RTECS #:EP1400000

Fraction by Wt: 25%

ACGIH TLV:50 PPM

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BE

NZIN)  
CAS:8030-30-6  
RTECS #:DE3030000  
Fraction by Wt: 25%  
OSHA PEL:100 PPM

Ingred Name:N-AMYL ACETATE (SARA III)  
CAS:628-63-7  
RTECS #:AJ1925000  
Fraction by Wt: 10%  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:EYE,THROAT,SKIN, LUNG,IRRITANT

===== First Aid Measures =====

First Aid:WASH SKIN THOROUGHLY FLUSH EYES WITH WATER,RE  
MOVE TO FRESH  
AIR,REMOVE CONTAMINATED CLOTHING GIVE ARTIF.RESP.IF NEEDED,CALL  
DOCTOR,DO NOT INDUCE VOMITING

===== Fire Fighting Measures =====

Flash Point:76F,24C TCC  
Lower Limits:1.0  
Extinguishing Media:FOAM,DRY CHEMICAL,FOG,CARBON DIOXIDE  
Fire Fighting Procedures:DO NOT USE H2O  
Unusual Fire/Explosion Hazard:AVOID FIRE,HEAT,SPARKS,NGNITION  
SOURCES,STORAGE IN DIRECT SUNLIGHT.

===== Accidental Release Measures =====

Spi  
II Release Procedures:VENTILATE AREA MECHANICALLU,KEEP FROM  
FLAME,FIRE,SPARKS,IGNITION SOURCES.DO NOT BREATHE VAPORS;CLEAN UP  
WITH ABSORBENT MATERIAL

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED,UPRIGHT,AWAY  
FROM FIRE,FLAME,SPARKS,IGNITION SOURCES,DIRECT SUNLIGHT  
Other Precautions:GROUND CONTAINERS WHILE POORING

===== Exposure Controls/Personal Protection =====

Respiratory Protection:

APPROVED BUREAU OF MINES DEVICE FOR TYPE AREA

Ventilation:LOCAL EXHAUST,GENERAL DILUTION

Protective Gloves:GLOVES,

Eye Protection:GOGGLES/GLASSES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:239F,115C

Vapor Pres:6.2

Vapor Density:>AIR

Spec Gravity:.855

Solubility in Water:MODERATE

Appearance and Odor:WHITE LIQUID

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:AVOID HEAT,SPARKS

Hazardous Decomposition Products:CO

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL  
REGULATIONS,DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United

States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.