

GRAYBAR ELECTRIC CO (DIST),GENERAL ELECTRICAL (MFR) -- 7526F -- 5970-00-162-7523

=====
Product Identification
=====

Product ID:7526F

MSDS Date:01/01/1985

FSC:5970

NIIN:00-162-7523

MSDS Number: BDDQF

=== Responsible Party ===

Company Name:GRAYBAR ELECTRIC CO (DIST),GENERAL ELECTRICAL (MFR)

Address:1 CAMPBELL RD

City:SCHEENECTADY

State:NY

ZIP:12306-9701

Country:US

Emergency Phone Num:800-626-2004

CAGE

:1B241

=== Contractor Identification ===

Company Name:GRAYBAR ELECTRIC CO INC

Address:1510 TOMLYNN ST

Box:City:RICHMOND

State:VA

ZIP:23230-3313

Country:US

Phone:804-359-1381

CAGE:1B241

Company Name:INSULATING MATERIALS INC

Address:1 CAMPBELL RD

Box:1404

City:SCHEENECTADY

State:NY

ZIP:12306-9701

Country:US

Phone:518-395-3300

CAGE:08800

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by

Wt: 5.8%-
OSHA PEL:100 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 46.5%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PENTACHLOROPHENOL (SARA III)
CAS:87-86-5
RTECS #:SM6300000
Fraction by Wt: 3.0%
OSHA PEL:S, 0.5 MG/M3
ACGIH TLV:S, 0.5 MG/M3; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

=====
Hazards Identification
=====

Effects of Over
exposure:MARKED NASAL IRRITATION,INGESTION-METABOLIC
STIMULATION,HYPERTHEMIA,MILD DEPRESSION,LOSS CONSCIOUS

=====
First Aid Measures
=====

First Aid:FLUSH EYES WITH WATER, REMOVE CONTAM CLOTHING & WASH
SKIN.FLUSH SIN WITH WATER. IF OVERCOME BY VAPOR,REMOVE FROM
EXPOSURE IMMEDIATELY,CALL MD. IF BREATHING IS STOPPED OR IRREGULAR,
START RESUSCITATION ADMINISTER OXYGEN.

=====
Fire Fighting Measures
=====

Fla
sh Point:60F PMCC
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:WATER FOG, FOAM, CO2,DRY CHEMICAL
Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED
AREAS.
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP PEOPLE
AWAY.REMOVE FREE LIQUID,ADD ABSRBENT TO SPILL AREA.AVOID BREATHING
VAPORS.VENTILATE ENCLOSED SPA

CES.OPEN ALL WINDOWS & DOORS, USE
PROPER PROTECTIVE EQUIPMENT. CLEAN UP ALL TRACES, SHOVEL INTO
CLEAN DRY CONTAIN

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID BREATHING DUSTS IF GENERATED
AVOID SKIN & EYE CONTACT. KEEP CONTAINERS CLOSED. KEEP AWAY FROM
HEAT & OPEN FLAME. USE ONLY WITH ADEQUATE VENTILAT

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:HYDROCARBON VAPOR CANI
STER, SUPPLIED-AIR OR A
HOSE MASK
Ventilation:FACE VELOCITY >60 FPM;USING LOCAL EXHAUST MECH. EXPL. PROOF
Protective Gloves:RUBBER
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:FACE SPLASH SHIELD;HYDROCARBON-INSOLUBLE
APRONG (NEOPRENE)
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:>138.3C, 281.F
Vapor Density:3.7
Spec Gravity:>0.70
Evaporation Rate & Reference:>1.0, BUTYL ACETAT
Solubility in Water
:NEGLIGIBLE
Appearance and Odor:WATER-WHITE COLOR,AROMATIC HYDROCARBON ODOR
Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
OXYGEN AND STRONG OXIDANTS,PLASTICS RUBBER
Stability Condition to Avoid:HIGH TEMPERATURE OF HEAT
Hazardous Decomposition Products:INCOMPLETE COMBUSTION PRODUCES CARBON
MONOXIDE
Conditions to Avoid Polymerization:TEMPERATURES EXCEEDING 392F

=====
Disposal Con
=====

siderations =====

Waste Disposal Methods:RECOVER FREE LIQUID.STAY UPWIND AND/OR USE
PERSONAL PROTECTIVE EQUIPMENT,ABSORB WITH DRY SELIDS & INCINERATE
UNDER APPROVED CONTROLLED PROCEDURES.RUN-OFF TO WATER CREATES FIRE
HAZARD.NOTIFY FIRE & HEA LTH AGENCIES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
exp
ressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.