

GRAYBAR ELECTRIC CO (DIST),GENERAL ELECTRICAL (MFR) -- 7526F -- 5970-00-162-7523

=====  
Product Identification  
=====

Product ID:7526F

MSDS Date:01/01/1985

FSC:5970

NIIN:00-162-7523

MSDS Number: BDDQF

=== Responsible Party ===

Company Name:GRAYBAR ELECTRIC CO (DIST),GENERAL ELECTRICAL (MFR)

Address:1 CAMPBELL RD

City:SCHEENECTADY

State:NY

ZIP:12306-9701

Country:US

Emergency Phone Num:800-626-2004

CAGE

:1B241

=== Contractor Identification ===

Company Name:GRAYBAR ELECTRIC CO INC

Address:1510 TOMLYNN ST

Box:City:RICHMOND

State:VA

ZIP:23230-3313

Country:US

Phone:804-359-1381

CAGE:1B241

Company Name:INSULATING MATERIALS INC

Address:1 CAMPBELL RD

Box:1404

City:SCHEENECTADY

State:NY

ZIP:12306-9701

Country:US

Phone:518-395-3300

CAGE:08800

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by

Wt: 5.8%-  
OSHA PEL:100 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 46.5%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PENTACHLOROPHENOL (SARA III)  
CAS:87-86-5  
RTECS #:SM6300000  
Fraction by Wt: 3.0%  
OSHA PEL:S, 0.5 MG/M3  
ACGIH TLV:S, 0.5 MG/M3; 9192  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

=====  
Hazards Identification  
=====

Effects of Over  
exposure:MARKED NASAL IRRITATION,INGESTION-METABOLIC  
STIMULATION,HYPERTHEMIA,MILD DEPRESSION,LOSS CONSCIOUS

=====  
First Aid Measures  
=====

First Aid:FLUSH EYES WITH WATER, REMOVE CONTAM CLOTHING & WASH  
SKIN.FLUSH SIN WITH WATER. IF OVERCOME BY VAPOR,REMOVE FROM  
EXPOSURE IMMEDIATELY,CALL MD. IF BREATHING IS STOPPED OR IRREGULAR,  
START RESUSCITATION ADMINISTER OXYGEN.

=====  
Fire Fighting Measures  
=====

Fla  
sh Point:60F PMCC  
Lower Limits:1.0  
Upper Limits:7.0  
Extinguishing Media:WATER FOG, FOAM, CO2,DRY CHEMICAL  
Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED  
AREAS.  
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP PEOPLE  
AWAY.REMOVE FREE LIQUID,ADD ABSRBENT TO SPILL AREA.AVOID BREATHING  
VAPORS.VENTILATE ENCLOSED SPA

CES.OPEN ALL WINDOWS & DOORS, USE  
PROPER PROTECTIVE EQUIPMENT. CLEAN UP ALL TRACES, SHOVEL INTO  
CLEAN DRY CONTAIN

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID BREATHING DUSTS IF GENERATED  
AVOID SKIN & EYE CONTACT. KEEP CONTAINERS CLOSED. KEEP AWAY FROM  
HEAT & OPEN FLAME. USE ONLY WITH ADEQUATE VENTILAT

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:HYDROCARBON VAPOR CANI  
STER, SUPPLIED-AIR OR A  
HOSE MASK  
Ventilation:FACE VELOCITY >60 FPM;USING LOCAL EXHAUST MECH. EXPL. PROOF  
Protective Gloves:RUBBER  
Eye Protection:CHEMICAL GOGGLES  
Other Protective Equipment:FACE SPLASH SHIELD;HYDROCARBON-INSOLUBLE  
APRONG (NEOPRENE)  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:F2  
Boiling Pt:>138.3C, 281.F  
Vapor Density:3.7  
Spec Gravity:>0.70  
Evaporation Rate & Reference:>1.0, BUTYL ACETAT  
Solubility in Water  
:NEGLIGIBLE  
Appearance and Odor:WATER-WHITE COLOR,AROMATIC HYDROCARBON ODOR  
Percent Volatiles by Volume:100

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
OXYGEN AND STRONG OXIDANTS,PLASTICS RUBBER  
Stability Condition to Avoid:HIGH TEMPERATURE OF HEAT  
Hazardous Decomposition Products:INCOMPLETE COMBUSTION PRODUCES CARBON  
MONOXIDE  
Conditions to Avoid Polymerization:TEMPERATURES EXCEEDING 392F

=====  
Disposal Con  
=====

siderations =====

Waste Disposal Methods:RECOVER FREE LIQUID.STAY UPWIND AND/OR USE  
PERSONAL PROTECTIVE EQUIPMENT,ABSORB WITH DRY SELIDS & INCINERATE  
UNDER APPROVED CONTROLLED PROCEDURES.RUN-OFF TO WATER CREATES FIRE  
HAZARD.NOTIFY FIRE & HEA LTH AGENCIES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
exp  
ressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.