

AKZO COATINGS INC -- BOSTIK (CAT-A-LAC) -- 8010-00-165-6548

=====
Product Identification
=====

Product ID:BOSTIK (CAT-A-LAC)

MSDS Date:01/01/1985

FSC:8010

NIIN:00-165-6548

MSDS Number: BDDWK

=== Responsible Party ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

City:ORANGE

State:CA

ZIP:92661

Country:US

Info Phone Num:714-637-1750

Emergency Phone Num:714-637-1750; CHEMTREC 800-424-93

00

CAGE:98502

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN

Fraction by Wt: 24.3%

Ingred Name:AMINE ADDUCT

Fraction by Wt: 4.0%

ACGIH TLV:N.A

Ingred Name:INERT PIGMENT

Ingred Name:HYDROCARBON SOLVENTS (XYLENE, TOLUENE, MEK, MIBK, MNBK,
N-BUTYL ALCOHOL,

BUTYL
Fraction by Wt: 49.7%
ACGIH TLV:100-200 PPM

Ingred Name:CELLOSOLVE & ISOPROPYL ALCOHOL)

=====
===== Hazards Identification =====

Effects of Overexposure:BREATHING VAPOR WILL BE IRRITATING TO NOSE AND THROAT. MAY CAUSE NAUSEA AND VOMITING.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE VICTIM TO FRESH AIR, CONSULT PHYSICIAN.
SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. EYES: FLUSH WITH WATER. CO
NSULT PHYSICIAN. INGESTION: INDUCE VOMITING. CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:28F, T.O.C.
Lower Limits:1.1
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL-TYPE FOAM
Fire Fighting Procedures:WATER MAY BE USED IN A FINE SPRAY TO COOL
Unusual Fire/Explosion Hazard:DO NOT APPLY TO HEATED SURFACES OR IN AREAS WHERE ELECTRICAL SPARKS MAY BE PRESENT.

=====
===== Accidental Release Measures =====

=

Spill Release Procedures:ABSORB MATERIAL WITH SAWDUST OR OIL-ABSORBING COMPOUND. WASH AREA WITH DETERGENT ANDATER. USE ADEQUATE VENTILATION TO CLEAR FUMES FROM AREA. AVOID SPARKS.

=====
===== Handling and Storage =====

Other Precautions:STORE UNDER 100F.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR-SUPPLIED RESPIRATOR OR SUITABLE CHEMICAL CARTRIDGE & DUST FILTER
Ventilation:FRESH AIR REQUIREMENTS WI

LL BE 18,000-20,000 CFM.

Protective Gloves:SOLVENT RESISTN

Eye Protection:GOGGLES OR FACE SHIELDS

Other Protective Equipment:COVERALLS, APRON, NON-SPARKING SAFETY SHOES.

Supplemental Safety and Health

ALSO CONTAINS 20% COLOR PIGMENT, 2% SUSPENSION AND FLOW ADDITIVES.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:170-340F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:STORAGE AT HIGH TEMPERATURES

Hazardous Decomposition Products:CARBON MONOXIDE, VARIOUS PIGMENT
COMBUSTION PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE WITH CARE. SANITARY LAND FILL
PREFERRED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for

use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.